

AN ISO 9001 : 2008 CERTIFIED COMPANY  
**SERVOKON**  
 रखे सब कन्ट्रोल में

Available on  
 DGS&D  
 Rate Contract

Digital Servo  
**Stabilizer**

1 KVA to 3000 KVA

3 PHASE VARIAC  
 2 AMP to 1200 AMP

Online UPS



## SERVOKON SYSTEMS LIMITED

Servokon House, C-13, Radhu Palace Road, Opp. Scope Minar,  
 Laxmi Nagar, Delhi-110092 Fax: 011-22415772 •  
 Mobile: 9810630786, 9311630786, 9310630786  
 E-mail: servokon@rediffmail.com • Visit us at: www.servokon.net

DEALERSHIP ENQUIRIES SOLICITED

**LT** Lutron

**WAGO**



2000A DC/1500A AC  
 TRUE RMS CLAMP METER

OTHER PRODUCTS AVAILABLE:

LUX METER, TORQUE METER, ACA LEAKAGE TESTER,  
 OXYGEN METER, CO2 METER, HUMIDITY, TEMP METER,  
 PH METER, INFRARED THERMOMETER & Many More Ranges

Contact for further details:

**Techno Instruments**

#2, P.M. Lane, S.P. Road Cross, Bangalore - 560 002.  
 Tel.: 91 80 41518739 Mobile: 9749335431/9740009967  
 Email: technoinstrument09@gmail.com

## WORLD CLASS RESISTORS FROM HTR



### WIRE WOUND RESISTORS

#### HIA/HTA

Power Axial type.  
 Power Rating: 0.5W to 20W  
 Resistance Range: R01 to 120K  
 Tolerances Available:  
 10%, 5%, 3%, 1%, 0.5%, 0.25%  
**Features:** • Flame retardant "Thermocoat"  
 • Precision. • Pulse types available.  
 • Non-inductive types available.

#### HFP

Power type PCB mounting.  
 Power Rating: 2W to 8W (at 70°C)  
 Resistance Range: R10 to 56K  
 Tolerances Available: 10%, 5%  
**Features:** • Low cost. Automated assembly  
 and wave soldering possible.  
 • Commercial applications.

#### HMV

Flat vertical mounting type.  
 Power Rating: 2.5W to 10W (70°C)  
 Resistance Range: R10 to 36K  
 Tolerances Available: 10%, 5%, 3%, 2%, 1%  
**Features:** • Ceramic legs act as heat sink.  
 • Slim profile. • Space saver.  
 • Pulse type available.  
 Available in low ohm current  
 sense type as HMVL series.

### CURRENT SENSE RESISTORS

#### BR

Slim type Metal Plate/  
 Preformed Resistance Strip.  
 Power Rating: 2W to 10W (70°C)  
 Resistance Range: R01 to 1R2  
 Tolerances Available: 10%, 5%  
**Features:** • Radial configuration.  
 • Negligible inductance. • Choice of 3 different  
 preformings available.

#### QA/QP

Open Frame / Axial and  
 PCB Mounting - Shunt Type.  
 Power Rating: 0.5W to 5W (85°C)  
 Resistance Range: R002 to R10  
 Tolerances Available: 10%, 5%, 3%, 2%, 1%  
**Features:** • Non insulated. • Surge /  
 current sensing applications.

#### OFSC

PCB mounting.  
 Power Rating: 10W (70°C)  
 Resistance Range: R0004 to R003  
 Tolerances Available: 5%, 3%, 2%, 1.5%, 1%  
**Features:** • Silicone Coated.  
 • Surge / current sensing applications.  
 • Negligible Inductance.

**HI-TECH RESISTORS PVT. LTD.**

AN ISO 9001:2008 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA

Tel. : +91-712-2531134, 2533269, 2553691. Fax : +91-712-2528334, 2558351. e-mail : info@htr-india.com | www.htr-india.com

