

Hall Sensors (USA)

www.magnesensor.com

Features

MH187

(General-Purpose Hall Effect Latch)

Open-Drain pre-driver.

Typical 30 Gauss

MH189

(Ultra High Sensitivity Hall Effect Sensor)

Chopper Stabilized amplifier stage

A short, circuit protected Pull-up resistor output

Ultra High sensitivity Typical 15 Gauss

MH187 pin to pin to US1881/US2881/ A 3282 / A 3280

MH189 pin to pin EW512 / EW732



Hall IC Latch - 182



Hall IC Omni Polar - 249



Hall IC Latch & Uni Polar - 187 / 281 / 282



Hall IC Linear - 481 / 482




Hall IC Unipolar & Latch - 182 / 186 / 282




MH 181/187/189/276
used on DC Fan

One chip solution MH 276

1. Hall sensor integrated with Transistor driver
2. One Chip Fan Driver IC



MH 181/187/189 used on Hall IC + Transistor driver DC Fan



1. 125 0 C
2. Green Package(Sony Standard) , Halogen Free.
3. Customer base:
HP, Toshiba, Acer, Fujitsu, Sony, Garmin, Nokia
4. ASIC Capability

Pin to Pin match

MH248ESQ - AH180-SNG-7/AH180-FJG-7

MH187 - US1881/US2881/A3282/A3280

MH189 - EW512/EW732

Ultrasonic sensor module

Range of measurement

0.03 ~ 3 M

Rated working voltage

5 VDC

Frequency of sensor

40 KHz



Ultrasonic Detector

Detect distance range: 150~600MM

Measuring mode:

direct reflection

(liquid level, solid level) 5-18VDC



- Linear 0-100% RH
- High performance
- Long Term Stability
- Close tolerance • Low Cost

Humidity Sensor

PRESSURE SENSORS Smartec, Netherlands



Absolute / Differential / Gauge type Output - Analogue / Digital / Bridge

Gas Modules



For Methane

NDIR

For CO

Combustible gas
(LPG / Natural)

RELAY -CE, UL, TuV, CQC certified

Telecom
General
Automotive relay



Micro Impex

IMPORTERS OF ELECTRONIC COMPONENTS & SENSORS

Shop No. 3, Ground Floor, Old Hanuman Bldg., Chunan Lane,
Off. Lamington Rd., Grant Road (East), Mumbai - 400 007. INDIA

Tel : 91-22-2388 6699 / 2389 6478 Fax : 91-22-2382 2176

Email : sales@microimpex.in / microimpex@vsnl.com

www.microimpex.com / www.microimpex.in

PIR Modules



Compact Size

DC3V 20V

Delay time 5s to 18min

TTL output can be directly connected to micro controller or logic device High sensitivity



Other Sensors :

Laser / Reflective / Photodiode
/IRLED / Phototransistor / Fluid

We can provide you import facility for your product with most reasonable price with MODVAT / CENVAT facility.