

Automotive

ROHM offers comprehensive support with a complete array of products optimized for the automotive market

Air conditioner | Instrument/ AC panel | Rain sensor | Mirror ECU | Body control | TPMS | Air bag | ABS | Engine control | EPS | Camera Module / Network | Stop lamp

Pb Free ROHM Electronic Components

RoHS Directive Compliance

IC Product Specifications



Voltage Trackers

	Part No.	Offset Voltage (mV)	Output Current (A)	Maximum Voltage(V)	Circuit Current (μA)	Operating Temperature(°C)
New	**BD3925FP**	±15 (Ta=–40 to +125°C, Vcc=6-36V, Io=5-200mA)	0.5	50	45	–40 to +125
New	**BD3925HFP**	±15 (Ta=–40 to +125°C, Vcc=6-36V, Io=5-200mA)	0.5	50	45	–40 to +125

High-reliability Serial EEPROMs

Part No.	Density (bit)	Supply Voltage Range (V)	Operating Temperature Range(°C)	Lifetime (times) (Ta=25°C)	Data Retention (yrs) (Ta=25°C)
BR25H□□0 series	1K to 32K	2.5 to 5.5	–40 to +125	10^6	40
BR93H□□ series	2K to 16K	2.7 to 5.5	–40 to +125	10^6	40

High Voltage LDO Regulators

	Part No.	Output Voltage (V)	Output Voltage Precision (%)	Output Current (A)	Maximum Voltage(V)	Circuit Current (μA)	Operating Temperature(°C)
New	**BD3570FP**	3.3	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3570HFP**	3.3	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3571FP**	5.0	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3571HFP**	5.0	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3572FP**	Variable	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3572HFP**	Variable	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3573FP**	3.3	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3573HFP**	3.3	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3574FP**	5.0	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3574HFP**	5.0	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3575FP**	Variable	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125
New	**BD3575HFP**	Variable	±2 (Ta=–40 to +125°C)	0.5	50	30	–40 to +125

Regulators with Voltage Detector and Watchdog Timer

	Part No.	LDO				Reset		
		Output Voltage(V)	Output Voltage Precision(%)	Output Current(A)	Saturation Voltage(V)	Detection Voltage(V)	Voltage Detector Precision(%)	Function
	BD3004HFP	5	±2 (Ta=–40 to +125°C)	0.5	0.78 (Io=200mA)	Variable (at Vs open : 4.1V)	±2	Adjustable Voltage Detector+WDT
	BD3005HFP	5	±2 (Ta=–40 to +125°C)	0.5	0.78 (Io=200mA)	4.5	±2	4.5V Voltage Detector +WDT(Active switch)
New	**BD3010AFV**	5	±2 (Ta=–40 to +125°C)	0.2	0.25 (Io=150mA)	Variable (at RADI open : 4.25V)	±3	Adjustable Voltage Detector+WDT

Flexible Step-down Switching Regulators with Built-in Power MOSFET

Part No.	Supply Voltage (V)	Output Current (A)	Output Voltage(V)	Reference Voltage Accuracy (%)	Operating Temperature (°C)	Oscillation Circuit
BD9001F	7 to 48	2.0	1 to VIN	±2	–40 to +95	Self-oscillation
BD9778F	7 to 35	2.0	1 to VIN	±2	–40 to +125	Self-oscillation
BD9778HFP	7 to 35	2.0	1 to VIN	±2	–40 to +125	Self-oscillation
BD9781HFP	7 to 35	4.0	1 to VIN	±2	–40 to +125	Self-oscillation/ External synchronization

Automotive Grade Operational Amplifiers/Comparators

Operational Amplifiers: Ground Sense

	Part No.	Number of Circuits	Supply Voltage (V)	Circuit Current (mA)	Input Offset Voltage (mV)	Slew Rate (V/μs)	Gain Bandwidth (MHz)
New	**BA2904HFVM-C**	2	3 to 32	0.7	2	0.2	0.5
New	**BA2902HFV-C**	4	3 to 32	0.7	2	0.2	0.5

Comparators: Ground Sense

	Part No.	Number of Circuits	Supply Voltage (V)	Circuit Current (mA)	Input Offset Voltage (mV)	Input Bias Current (nA)	Output Current (mA)	Input Voltage Range (V)
New	**BA2903HFVM-C**	2	2 to 36	0.6	2	50	16	VEE to VCC–1.5
New	**BA2901HFV-C**	4	2 to 36	0.8	2	50	16	VEE to VCC–1.5

LED Driver IC for Indicators

Part No.	Power Supply (V)	Output Current (mA)	Number of Inputs	Number of Outputs	Output Type	Maximum Voltage(V)
BD8105FV	4.5 to 5.5	50	5	12	Open Drain	35

Discrete Product Specifications

MOSFETs

Part No.	Package	Polarity	VDSS (V)	ID (A)	PD(W) (Ta=25°C)	RDS(on) Typ. (mΩ)			Qg (nC)	Driving Voltage(V)
						VGS=4V	VGS=4.5V	VGS=10V		
RSS090N03	SOP8	Nch	30	9	2	17	15	11	11	4
RSS085N05	SOP8	Nch	45	8.5	2	18	16	13	15.3	4
RSS065N06	SOP8	Nch	60	6.5	2	31	28	24	11	4
RSS075P03	SOP8	Pch	–30	–7.5	2	25	22	15	30	4
RSS060P05	SOP8	Pch	–45	–6	2	38	35	26	23	4
SP8K3	SOP8	Nch+Nch	30	7	2	25	23	17	8.4	4
SP8J1	SOP8	Pch+Pch	–30	–5	2	45	40	30	16	4
SP8M3	SOP8	Nch	30	5	2	58	52	36	3.9	4
		Pch	–30	–4.5		65	57	40	8.5	4
RSQ045N03	TSMT6	Nch	30	4.5	1.25	40	36	27	6.8	4
RSQ035P03	TSMT6	Pch	–30	–3.5	1.25	70	65	45	9.2	4

Transistors for Solenoid Motors

Part No.	Package	Polarity	VCC (V)	IO (A)	PD(mW) (Ta=25°C)	GI	R1/R2 (kΩ)
DTDG14GP	MPT3	NPN	60±10	1	500	300 or more	none/10
DTDG23YP	MPT3	NPN	60±10	1	500	300 or more	2.2/10
2SD2143	CPT3	NPN	60±10	2	1000	1k to 10k	3.5/0.3
QSH29	TSMT6	NPN+NPN	60±10	0.5	500	500 or more	none/10

Rectifier Diodes

Part No.	Package	VRM (V)	IO (A)	IFSM (A)
RR264M-400	PMDU	400	0.7	25
RR274EA-400	TSMD5	400	0.5	8

General Purpose ICs
Video and Imaging ICs
Audio ICs
IT Equipment ICs
Consumer Product ICs
Automotive ICs
Discrete Semiconductors
Passive Components
Optoelectronics
Modules

ROHM Semiconductor
Singapore Pte. Ltd.
(India Representative Office)
Unit 103, 1st Floor,
Raheja Towers, Annasalai,
Chennai -600 002, India
Telephone: +91-44-43520008

ROHM Semiconductor
Singapore Pte. Ltd.
9 Temasek Boulevard
#21-01/02/03
SUNTEC TOWER 2
Singapore - 038989
Telephone: +65- 6332-2322

ROHM Co., Ltd.
21 Saiin Mizosaki-cho, Ukyo-ku,
Kyoto 615-8585 Japan
TEL : +81-75-311-2121 FAX : +81-75-315-0172

www.rohm.com

ROHM SEMICONDUCTOR