



no harmful effects from water, greater than 87 per cent efficiency and the ability to power the SD30 with solar-power collecting batteries, this LED floodlight is an eco-friendly way to enjoy nocturnal nature trails.

Acro Engineering, New Delhi
Phone: (011) 40525645

24-LED panels for streetlights

Vishay Intertechnology has broadened its optoelectronics portfolio with new LED light panels for streetlight and industrial overhead lighting applications. The panels double as the core of a development kit that gives designers everything they need to get up to speed designing with Vishay's solid-state lighting solutions.

In addition to the 4x6-LED panel, the kit includes reflectors and a driver module, providing the basic tools that designers need to avoid development delays and focus on launching lighting products to market quickly.

Two panel options are available: The VLSL30 features cool white LEDs with temperature range of 5000°K to 7000°K and luminous flux of 2160 lumens. The VLSL31 features neutral white LEDs with temperature range of 3800°K to 5000°K and luminous flux of 1900 lumens.

Vishay Components India Pvt Ltd, Bengaluru
Fax: (080) 25584291
Phone: 25586277
E-mail: business-asia@Vishay.com

SECURITY

OSD cameras

Sparsh has extended its line of high-resolution security cameras by launching the Bravura 540 TVL OSD series.



The Bravura camera series is based on Sony Super HAD-II CCD technology and further improves the video quality of security surveillance, expanding applications for security cameras.

Key features enabled by Bravura series are selective backlight compensation, privacy masking, highlight suppress backlight compensation and on-screen display.

Samridhi Automations P Ltd, Noida
Phone: (0120) 4518900
E-mail: info@sparshsecuretech.com

TEST & MEASUREMENT

High-performance spectrum analyser

The compact, economical R&S FSC spectrum analyser from Rohde & Schwarz covers a frequency range of 9 kHz to either 3 GHz or 6 GHz. In its



class, the analyser is said to achieve top RF performance metrics. With a maximum sensitivity of -161 dBm (1 Hz), it can capture even weak signals. Its low-level measurement uncertainty of less than 1 dB ensures accurate results.

The analyser is perfect for those who need basic functions such as noise marker, frequency counter, modulation depth measurement of AM signals or power measurement of pulsed signals. In both frequency ranges, the R&S FSC is available with an internal tracking generator that provides additional functionality such as cable-loss measurements and simple determination of transmission characteristics of DUTs (filters, amplifiers, etc).

The analyser is suitable for installation in small and mobile test systems.

Rohde & Schwarz, New Delhi
Fax: (011) 42535433
Phone: 42535400
E-mail: sales@rsindia.rohde-schwarz.com
Web: www.rohde-schwarz.co.in

3%-digit multimeter

KUSAM-MECO has introduced a UL-approved, 3%-digit, 6000-count digital multimeter (model KM-255/KM-257) with LCD, electric field detection and



computer interface.

The multimeter features transient protection up to 6.5 kV and T_{RMS} function. It can measure AC/DC voltage (60 mV to 1000 V), AC/DC current (600 μ A to 8.00A), capacitance (60.00 nF to 3000 μ F), temperature (50°C to 1000°C) and resistance (600.0 ohms to 60.00 mega-ohms). It is also capable of diode testing, non-contact electric field detection up to 1000V and logic level testing (5.00 Hz to 1.000 MHz).

Kusam Electrical Industries Ltd, Mumbai
Fax: (022) 24149659
Phone: (022) 24156638, 24124540, 24181649
E-mail: kusam_meco@vsnl.net,
sales@kusam-meco.co.in
Web: www.kusam-meco.co.in,
www.kusamelectrical.com

TOOLS & EQUIPMENT

RFID reader

The Serial TTL RFID reader from rhydoLABZ reads EM4100 family transponder tags that are brought in proximity to the reader and outputs the unique tag identification number through serial port at 9600 bps (TTL format). The TTL output from the reader allows the user to interface it directly with 5V micro-controllers. The reader outputs twelve bytes including one start byte, one stop byte and ten unique data bytes. Start and stop bytes ensure that a correct string has been received from the reader. The middle ten bytes are the actual tag's unique ID. Vertical and horizontal parity checking in the card reading algorithm ensures data integrity.

The board has a power-indication LED and a status LED to indicate card detection. The normal detection range is 10-15 cm for card type tags.

The reader is priced at Rs 1590.