

Rhydo Technologies Pvt Ltd, Cochin, Kerala
Fax: (0484) 2370579
Phone: 2370444, 2371666
E-mail: sales@rhydolabz.com
Web: www.rhydolabz.com

COMPUTING

Eco-friendly graphics card

ASUS' Bravo220 home entertainment PC card provides cutting-edge visual fidelity while saving energy. Its thermal landscape balances thrifty operation with the need for uncompromising



performance as a multimedia anchor, resulting in 21 per cent better power efficiency compared to competing models. The cooling solution also boasts of silent 0dB operation, with no fans needed. Instead, Bravo220 uses oversized heat-sinks and advanced materials to ensure quick heat dissipation and greater longevity, without falling back on power-hungry active cooling, thus minimising energy consumption.

ASUS Technology Pvt Ltd, Mumbai

Phone: (022) 67668800, 18002090365

E-mail: media_india@asus.com

Web: www.asus.in

PCI Express USB 3.0 expansion card

Transcend Information, Inc. has introduced a USB 3.0 expansion card that comes with two high-speed USB 3.0 ports. This easy-to-install add-on card enables speed enthusiasts to connect USB 3.0-compatible peripherals to their desktop PC and experience data transfer rates up to ten times faster than USB 2.0 with optimised power efficiency. The card's PCI Express 2.0 single-lane connection interface is compatible with virtually all current motherboards, and guarantees unrestricted two-way communication between the computer and any USB device plugged

into the card.

The two external USB ports fully support the USB 3.0 standard with connection bandwidth of up to 5 Gbps, which is ten times faster than USB 2.0 specifications.

Supertron, New Delhi

Phone: (011) 41318277

E-mail: vibhor@supertronindia.com

COMPONENTS

3-channel power management unit

Texas Instruments has introduced a small power management unit that supports portable consumer electronics and other space-constrained applications, such as webcams and heat-/noise-sensitive embedded camera modules.

Available in a 2x2mm² package, the TPS657051 features two 400mA step-down converters, a 200mA low-dropout linear regulator and additional supporting functions.

Texas Instruments (India) Pvt Ltd, Bengaluru

Fax: (080) 25048286

Phone: 25099221

Web: www.ti.com

Server processor

AMD has launched the Opteron 4000 Series platform that meets the specific requirements of cloud, hyperscale data centre and SMB customers needing highly flexible, reliable, and power-



efficient 1P and 2P systems. This platform is also available for high-end embedded systems such as telecom servers, storage and digital signage, through AMD Embedded Solutions.

The processor is ideal for custom-designed servers because it allows for smaller heat-sinks, power supplies and fans, as well as low-voltage memory to help improve power efficiency.

AMD Far East Ltd, New Delhi

Fax: (011) 41672623

Phone: 41672614

Signal-isolating transducer

Meco-G has introduced highly reliable, low-cost, accurate DC-isolation transducers that convert a DC signal like mV, mA, V and A into a standard

DC signal like 4-20 mA, 0-10V DC with optical isolation. The output is linearly proportional to the measured input signal.

The transducers have an accuracy of 0.5 per cent. These are available in a flame-retardant case and operate off 110V AC, 230V AC, 24V DC, 48V DC, 110V DC and 220V DC auxiliary supplies. They are suitable for telemetering, data loggers, PLCs, SCADA systems and control applications.

Goliya Instruments Pvt Ltd, Mumbai

Fax: (022) 24130747

Phone: 24149657, 24179467

E-mail: goliya@mtl.in

Web: www.goliyainstruments.com

Flyback controllers

Linear Technology has announced high-reliability military-temperature-grade versions of LTC3803/-3/-5 current-mode flyback controllers in the tiny 6-pin ThinSOT package. These devices are specified and production-tested over junction temperatures of -55°C to 150°C.

The input and output voltage ranges of LTC3803/-3/-5-based power supplies are limited only by external components, enabling wide-input-voltage and high-input-voltage applications commonly found in industrial, telecom, military and automotive settings. The constant 200kHz or 300kHz operating frequency is maintained down to very light loads, minimising low-frequency noise generation over a wide range of load current. An integrated soft-start function reduces inrush current and output voltage overshoot.

Arrow Electronics India Ltd, Bengaluru

Fax: (080) 5127784

Phone: 51353800