

RESISTORS SYNONYMOUS WITH QUALITY.



WIRE WOUND RESISTORS

HCA

Power Axial type
Power Rating : 1W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : ● High insulation.
● Fire proof. ● Resistant to aggressive solvents.
● Pulse type available.
● PCB requirements.
● Bracket acts as heat sink.

VHIA / HIA

Power Rating :
0.5W to 20W (40°C)
Resistance Range :
R01 to 120K
Tolerances Available :
10%, 5%, 2%, 1%
Features : ● Flame retardant
● Reduced temperature at PCB solder point.

HMV

Flat vertical mounting type.
Power Rating : 2.5W to 15W (70°C)
Resistance Range : R10 to 36K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features :
● Ceramic legs act as heat sink.
● Slim profile. ● Space saver.
● Pulse type available.
Available in low ohm current sense type as HMVL series.

HCP

Power Type
PCB Mounting
Power Rating : 3W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%
Features :
● Inverter / Power Supplier applications.
● Adaptable to automated assembly.
● Choice of terminal stand-off heights.
● Choice of terminals to suit exact PCB requirements.

HSR

Capacitor discharge,
Wire wound symmetry resistors
Power Rating :
8.25W & 11W (70°C)
Resistance Range :
10K to 70K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : ● Stainless steel mounting terminals for direct mounting on to capacitors.

CURRENT SENSE RESISTORS

OFSC

PCB mounting.
Power Rating :
5W & 10W (70°C)
Resistance Range: R00012 to R003
Tolerances Available:
5%, 3%, 2%, 1.5%, 1%
Features : ● Silicone Coated.
● Surge / current sensing applications.
● Negligible inductance.

RL

Alloy ribbon element
in cylindrical ceramic body.
Axial type.
Power Rating : 0.5W to 10W (25°C)
Resistance Range : R002 to R30
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features :
● Negligible Inductance.
● Replaces moulded type.

OA/OP

Open Frame /
Axial and PCB Mounting -
Shunt Type.
Power Rating : 0.5W to 5W (85°C)
Resistance Range : R002 to R10
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features :
● Non insulated.
● Surge / current sensing applications.

HI-TECH RESISTORS PVT. LTD.

AN ISO/TS 16949:
2002 CERTIFIED COMPANY

Buty Compound, Mount Road Extension,
Nagpur-440 001, INDIA.
Fax : +91-712-2528334, 2556351.
Tel : +91-712-2531134, 2532269, 2553691.
e-mail : info@htr-india.com
www.htr-india.com

SMD ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE
& PASSIVE COMPONENTS

Authorised Distributor

leaguer SMD E-Capacitors

KEXIN SMD Resistors
SMD LED SMD Diodes
SMD Capacitors

watts SMD Resistors

CHIP TRANSISTORS / CHIP DIODES / CHIP LED'S / CHIP CAPACITORS / CHIP IC'S

- | | | |
|--------------------------------|--------------------------------------|---------------------------|
| ● CHIP RESISTORS | ● CHIP BRIDGE RECTIFIERS | ● CHIP FERRITE BEADS |
| ● CHIP RESISTOR NETWORKS | ● CHIP TRANSIENT VOLTAGE SUPPRESSORS | ● CHIP HALL SENSORS |
| ● CHIP CAPACITORS | ● CHIP IC'S | ● CHIP IR LED'S & SENSORS |
| ● CHIP TANTALUM CAPACITORS | ● CHIP MODFETS | ● CHIP POTENTIOMETERS |
| ● CHIP ELECTROLYTIC CAPACITORS | ● CHIP REGULATORS | ● CHIP FUSES |
| ● CHIP ZENERS & DIODES | ● CHIP OPTO COUPLERS | ● CHIP SWITCH |
| ● CHIP TRANSISTORS | ● CHIP TRIMMER CAPACITORS | ● CHIP MOV'S |
| ● CHIP LED'S | ● CHIP INDUCTORS | ● CHIP THERMISTORS |
| ● CHIP SCHOTTKY DIODES | | ● CHIP SOLDER PASTE |
| | | ● CHIP SOLDER WIRE 26 SWG |



54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road,
Mumbai - 400 007, INDIA. Tel : 91-22-3240 2444 • Mob. : 93242 11912

E-mail : smdelectro@vsnl.net

STOCKIST OF ELECTRONIC COMPONENTS



Circuit Electro-Components Pvt. Ltd.



"Drug House", Bldg. 54-B, Proctor Road, Mumbai - 7, INDIA.
Pin Code : 400 007 • Tel : 2367 7777 / 2380 0888
Mob. : 93222 34370 / 93227 91112 • Fax : 91-22-2387 9335
E-mail : circuit@vsnl.com • Website : www.circuitelectro.com

MONDAY EVENING
AVAILABLE