



Automotive

ROHM offers comprehensive support with a complete array of products optimized for the automotive market



IC Product Specifications

Voltage Trackers

Part No.	Output Voltage (V)	Output Current (mA)	Input Current (mA)	Operating Temperature (°C)
BD3925FP	+5	0.5	50	-40 to +125
BD3925HP	+15	0.5	50	-40 to +125

High-reliability Serial EEPROMs

Part No.	Capacity (bits)	Supply Voltage Range (V)	Operating Temperature (°C)	Life Expectancy (years)	Data Retention (yr)
BR25HC30	1K to 32K	2.5 to 5.5	-40 to +125	10 ⁵	40
BR93HC30	2K to 16K	2.7 to 5.5	-40 to +125	10 ⁵	40

High Voltage LDO Regulators

Part No.	Input Voltage (V)	Output Voltage Precision (%)	Output Current (mA)	Maximum Voltage (V)	Input Current (mA)	Operating Temperature (°C)
BD3570FP	3.3	±2	0.5	50	30	-40 to +125
BD3570HP	3.3	±2	0.5	50	30	-40 to +125
BD3571FP	5.0	±2	0.5	50	30	-40 to +125
BD3571HP	5.0	±2	0.5	50	30	-40 to +125
BD3572FP	Variable	±2	0.5	50	30	-40 to +125
BD3572HP	Variable	±2	0.5	50	30	-40 to +125
BD3573FP	3.3	±2	0.5	50	30	-40 to +125
BD3573HP	3.3	±2	0.5	50	30	-40 to +125
BD3574FP	5.0	±2	0.5	50	30	-40 to +125
BD3574HP	5.0	±2	0.5	50	30	-40 to +125
BD3575FP	Variable	±2	0.5	50	30	-40 to +125
BD3575HP	Variable	±2	0.5	50	30	-40 to +125

Regulators with Voltage Detector and Watchdog Timer

Part No.	Input Voltage (V)	Output Voltage (V)	Output Current (mA)	Watchdog Time (ms)	Operating Temperature (°C)	Function
BD3004HP	5	+2	0.5	0.78 (100000A)	±2	Auto voltage detector
BD3005HP	5	+2	0.5	0.78 (100000A)	±2	Auto voltage detector
BD3016A5V	5	+2	0.25 (150000A)	Variable (in R2 pin, 4.0V)	±3	Auto voltage detector

Flexible Step-down Switching Regulators with Built-in Power MOSFET

Part No.	Input Voltage (V)	Output Voltage (V)	Output Current (mA)	Operating Temperature (°C)	Self-cooling
BD9001F	7 to 48	2.0	1 to 1V	±2	-40 to +45
BD9728F	7 to 35	2.0	1 to 1V	±2	-40 to +125
BD9728HP	7 to 35	2.0	1 to 1V	±2	-40 to +125
BD9781HP	7 to 35	4.0	1 to 1V	±2	-40 to +125

General Purpose ICs
Video and Imaging ICs
Audio ICs
IT Equipment ICs
Consumer Product ICs
Automotive ICs
Discrete Semiconductor Products
Passive Components
Optoelectronics
Modules

ROHM Semiconductor
Singapore Pte. Ltd.
(India Representative Office)
Unit 103, 1st Floor,
Rajeha Towers, Annasalai,
Chennai - 600 002, India
Telephone: +91-44 43520008

ROHM Semiconductor
Singapore Pte. Ltd.
9 Temasek Boulevard
#21-01/02/03
SUNTEC TOWER 2
Singapore - 038989
Telephone: +65-6332-2322

ROHM Co., Ltd.

21 San Misonaki-cho, Ukyo-ku,
Kyoto 615-8585, Japan
TEL: +81-75-311-2121 FAX: +81-75-315-0172

www.rohm.com



Automotive Grade Operational Amplifiers/Comparators

Operational Amplifiers: Ground Sense

Part No.	Number of Channels	Supply Voltage (V)	Input Current (mA)	Input Offset Voltage (mV)	Max Rate (V/μs)	Gain Bandwidth (MHz)
BA2904HPVM-C	2	3 to 32	0.7	2	0.2	0.5
BA2902HPV-C	4	3 to 32	0.7	2	0.2	0.5

Comparators: Ground Sense

Part No.	Number of Channels	Supply Voltage (V)	Input Current (mA)	Input Offset Voltage (mV)	Input Bias Current (nA)	Output Voltage Range (V)
BA2903HPV-C	2	2 to 36	0.6	2	50	V _{EE} to V _{CC} -1.5
BA2901HPV-C	4	2 to 36	0.8	2	50	V _{EE} to V _{CC} -1.5

LED Driver ICs for Indicators

Part No.	Power Supply (V)	Output Current (mA)	Number of Inputs	Number of Outputs	Output Type	Maximum Duty (%)
BD8105FV	4.5 to 5.5	50	5	12	Open Drain	35

Discrete Product Specifications

MOSFETs

Part No.	Package	Polarity	V _{DS} (V)	I _D (A)	P _D (W)	V _{GS} (V)	V _{DS(on)} (V)	r _{DS(on)} (mΩ)	Q _g (nC)	Q _{rr} (nC)	ft (MHz)
RS509N03	SO8P	Nch	30	9	2	17	15	11	11	4	
RS509N05	SO8P	Nch	45	8.5	2	18	16	13	15.3	4	
RS509N06	SO8P	Nch	60	6.5	2	31	28	24	11	4	
RS507S03	SO8P	Pch	-30	-7.5	2	25	22	15	30	4	
RS506P05	SO8P	Pch	-45	-6	2	36	35	26	23	4	
SP8K3	SO8P	Nch/Nch	30	-7	2	25	23	17	8.4	4	
SP8J1	SO8P	Pch/Pch	-30	-5	2	45	40	30	16	4	
SP8M3	SO8P	Nch	30	5	2	58	52	36	3.9	4	
RS0Q45N03	TSMT8	Nch	30	4.5	1.25	40	36	27	6.8	4	
RS0Q5P03	TSMT8	Pch	-30	-3.5	1.25	70	65	45	9.2	4	

Transistors for Sensor Motors

Part No.	Package	Polarity	V _{CE} (V)	I _C (A)	P _{DMOS} (W)	Q _g (nC)	f _T (MHz)
DTDG14GP	MP12	NPN	65x10	1	500	300 or more	none10
DTDG23YP	MP12	NPN	65x10	1	500	300 or more	2.2/10
25D2143	CPT3	NPN	65x10	2	1000	1k to 10k	3.5/10
Q5H29	TSMT8	NPN+NPN	65x10	1.5	500	500 or more	none10

Rectifier Diodes

Part No.	Package	V _{RRM} (V)	I _F (A)	Power (W)
RR264M-400	PM5U	400	0.7	35
RD274EA-400	TSMD5	400	0.5	6