

quality, comfort and durability for dealing with the special requirements in contact centre and office environments. In addition, these headsets are configured for business and contact centre professionals using standard desk phones operating in the 300-3400Hz frequency range. The in-built hand-made neodymium speakers provide maximum frequency response within this range, resulting in greater call clarity, fewer misunderstandings and better customer service all round.

The headsets are available with different microphones and noise-canceling systems to match any work environment. These come in mono or duo speaker configuration. All mono versions offer a choice of three wearing styles—earhook, neckband or headband.

Innovate Telecom, Delhi

Fax: (011) 22441991, 22441992

Phone: 22441991, 22441992, 42448678

E-mail: info@innovatelecom.com

SECURITY

Time-attendance and access control system

Matrix COSEC is a function-rich time-attendance and access control solution for small offices and home offices, small and medium enterprises, as well



as large enterprises. Its modular design allows scalability and supports ten to one million users. Unlike traditional solutions, Matrix access control solution is based on IP backbone and master-slave architecture. This ensures that the access control installation is no more a pain for the integrators.

The Matrix security product range includes management and reporting software for COSEC solutions, door controllers, exit readers, card personal-ity modules, additional hardware, and

optional software modules for visitor, employee and enrollment management.

Matrix Telecom, Vadodara

Fax: (0265) 2636598

Phone: 2630555

E-mail: mary.thomas@matrixcomsec.com

Web: matrixcomsec.com

Vehicle tracking system

Innovative Embedded Systems has launched an advanced vehicle tracking system with Web-based tracking (Website 'www.itracksolution.com'). Based on SiRF III chipset, the iTrack-P9 offers



20-channel tracking with tracking sensitivity as good as -157 dBm. This cost-effective solution has many state-of-the-art features like 4MB flash for data storage, internal Li+ backup battery, eight analogue/digital input outputs, one relay output for ignition or fuel pump control, USB interface for PC connectivity.

The iTrack-P9 is useful for fleet management, courier tracking, valuable asset tracking during movement and vehicle security.

Innovative Embedded Systems Pvt Ltd,

Roorkee (Haridwar)

E-mail: sales@iemsys.com

COMPUTING

Graphics cards

The new graphics cards from ASUS deliver the benefits of the debuting 40nm NVIDIA GPUs, offering considerable power improvements over their predecessors. These come in two



varieties. The flagship ENGTX480 uses the GTX480 core with 1401 stream processors and a 384-bit memory inter-

face. It is a frontline extreme performance board with a 700MHz core clock and 1536 MB of 3696MHz GDDR5 memory.

The powerful mainline ENGTX470 is a 1215-stream processor version of the NVIDIA GTX470 chip. It packs a 607MHz core and 1280 MB of GDDR5 RAM at 3348 MHz with a 320-bit interface.

ASUS Technology Pvt Ltd, Mumbai

Phone: (022) 67668800, 18002090365

E-mail: media_india@asus.com

Web: www.asus.in

Motherboard supporting multiple processors

Simtronics has launched a new motherboard that supports a wide range of Intel processors including Core 2 Quad, Core 2 Duo, Pentium D, Pentium 4 and Intel Celeron D.

SIMM-INT G-31 with Intel G31/ICH7 chipset is combined with Intel Core2 family processor. It offers major



advancements in video, graphics, responsiveness and scalability. The board is embedded with DDR2-800/667, 2x240-pin DDR2 DIMM socket, up to 4GB memory and eight channels of HD audio. It comes with PS2 mouse port, PS2 keyboard port, serial port, four USB ports, VGA port and multiple stereo input port.

The board is competitively priced at Rs 2500.

Simtronics Semiconductors Ltd, New Delhi

Phone: (011) 40570300

E-mail: sales@simtronics.com

POWER SUPPLY

Step-down DC-DC controller

Linear Technology has introduced a three-phase, single-output, high-efficiency (up to 95 per cent), synchronous, step-down DC-DC controller. The LTC3829 is capable of PolyPhase