

operation, differential output voltage sensing and integrated phased-lock loop (PLL) clock synchronisation. Up to six phases can be paralleled and clocked out of phase to minimise input and output filtering requirements for high-current (up to 150A) applications. The differential amplifier provides true remote output voltage sensing of both the positive and negative terminals, enabling highly accurate regulation independent of IR losses in trace runs, vias and interconnects.

Arrow Electronics India Ltd, Bengaluru

Fax: (080) 51127784

Phone: 51353800

TOOLS & EQUIPMENT

FPGA expansion board

Speeding the development of low-cost security access control systems and other applications that require a high-speed interface to external processing units, Texas Instruments Incorporated (TI) has launched the Stellaris FPGA expansion board for the DK-LM3S9B96 development kit. The new board enables developers to easily evaluate the high-bandwidth machine-to-machine (M2M) parallel interface capability of Stellaris microcontroller's flexible external peripheral interface.

Key features of the board include external peripheral interface (EPI) operation at 50 MHz for large amount of data logging and analysis, complete hardware, 1 MB of asynchronous 10ns SRAM for graphics/video buffers and 1 kilobit of PC memory for storing configuration data, eight FPGA test pads, and video and motion software features to jumpstart development. The board plugs directly into the EPI on the DK-LM3S9B96 development board.

Texas Instruments (India) Pvt Ltd, Bengaluru

Fax: (080) 25048286

Phone: 25099221

Web: www.ti.com

Wireless thermal printer

Evolute Systems, India, has launched a compact wireless thermal printer called 'IMPRESS' that can print up to 18 lines per second with 24 or 42 characters per

line. Once fully charged, the rechargeable 1500mAh Li-ion battery allows the printer to print over 2000 charge slips of 5 cm each. It can have a dual-track ISO 7813 magnetic card reader, dual ISO



7816 smart card reader and a contactless ISE/IEC 14443A smart card reader. A fingerprint scanner and a BAR code reader are add-on features.

The printer measures 12.2x8.2x4 cm³ and weighs 220 gm.

Evolute Systems Pvt Ltd, Bengaluru

Phone: (080) 42078037

E-mail: sales@evolute-sys.com

Web: www.evolute-sys.com

Single-phase thyristor modules

SanRex India has introduced MKKT series single-phase thyristor modules under the brand 'SanRex.' The new modules feature heat transfer through



aluminium-oxide ceramic-isolated metal base plate and heat-soldered joints for high reliability. These are available in 26, 41, 56, 95, 105, 162, 250, 330, 450 and 550 amps with blocking peak-inverse voltage of up to 1800.

SanRex Power Unlimited, Delhi

Fax: (011) 22528193

Phone: 22450669, 22443951, 22464894

E-mail: sanrexindia@gmail.com

Web: www.sanrexindia.com

Ethernet managed switch

Dax Networks has launched a range of high-performance L2 managed fast ethernet switches. Priced at Rs 49,000,

the DX-509MG series is ideal for retail applications and broadband distribution.

The DX-509MG series comprises three models: basic (DX-509MG), enhanced (DX-509MGE) and POE (DX-509MG-POE). The DX-509MG is designed for networks where the number



of users being connected is minimal. The presence of eight 10/100 ports, eight RJ45 connectors and one Gigabit combo uplink port makes it ideal for connecting end-point PCs at the access level in a campus network.

The enhanced version (DX-509MGE) supports IPv6/IPv4 dual stack, helping to protect the customers' investment. It also supports IPv6 host, manager and application.

Dax Networks Ltd, Chennai

Fax: (044) 42923567

Phone: 42923558, Ext. 550

E-mail: thirupura@dax.in

Web: www.daxnetworks.com

SOFTWARE

Digital communication simulator

Tetcos has launched a new digital communication simulator for the undergraduates' lab. PhySim allows the users to create baseband, RF, antenna and channel and receiver chain and comes with inbuilt oscilloscope, spectrum analyser and polar plot.

Using PhySim, you can cover all the experiments available with hardware trainers, but at less than half the total cost. Further, PhySim allows for easy upgradation and zero-maintenance cost. Easy-to-experiment library blocks make learning interactive and dynamic. The real-time results obtained are in tandem with real-time measuring devices.

Tetcos, Bengaluru

Telefax: (080) 2663624

E-mail: sales@tetcos.com

Web: www.tetcos.com