

GW Instek Programmable AC/DC Power Source

The APS-1102 multifunction programmable AC/DC power source from GW Instek comes with an arbitrary waveform generator. It allows programming of the outputs for simulation of a power source with abnormal variations. The APS-1102 includes a multifunctional and user-friendly software that supports remote control of panel operations, sequence editing and execution, arbitrary waveform editing and transfer, and data logging via USB interface. All these measurement readings and settings are displayed on a 14.5cm (5.7-inch) LCD screen simultaneously.

The equipment design includes a DC power source block, used to improve power factor of power supply input. The internal signal source with sequence function is used to provide AC+DC output. The APS-1102 can be used as an amplifier for external signal to generate power output depending on the selected mode and connected external signal. (For details, visit www.gwinstek.com/en/index.aspx)



AG Measurematics Computerised Lifting System

For the first time in India, a fully automated computerised system is designed to lift large to very large loads such as bridge piers, ships, railway wagons and locomotives in such a way that the lifted load remains oriented in the same way as it was standing on the ground. AG Measurematics' CylSyn converts direction-control hydraulic valves into digitally actuated hydraulic switches.

The system has an integrated controller that incorporates a computer with touch-screen monitor, wireless keyboard and mouse, high-speed data acquisition and control device, pressure sensors and long stroke extension type linear displacement transducers. The application software based on Windows is preloaded on the computer and the load is measured through a special pressure transducer that uses thin-film technology. (For details, visit www.agmpl.com/)

Today, multiple-input, multiple-output over-the-air (MIMO OTA) emulators are available to support the increased performance and data rates of MIMO mobile terminals. These can test relatively small devices such as terminals, antennae, smart phones and laptops, and usually fit into a complete test system comprising transmitters, a radio channel emulator and an anechoic chamber that includes multiple antennae reasonably spaced from the device under test. Such a system can test a device without requiring cable connections to it, and also perform end-to-end test of the device's antennae, radio frequency front-end, and base-band processor in a single operation. These systems are designed to meet the conformance-testing needs of several protocols including WCDMA, HSPA, 3GPP LTE, WiMAX and WLAN, and can help benchmark the performance of mobile devices for quality of service, data throughput, latency and spectrum availability.

Of late, we also find a few test systems capable of testing in parallel for various protocols including GSM, EDGE, CDMA One, W-CDMA, HSPA, HSPA+, CDMA-2000, EV-DO and LTE. Today's 3G and 4G handsets and other portable devices include multiple radios representing numerous standards. Traditional test methods involve attaching dummy loads to the handsets and test-



**NEW
ArbStudio™**
125 MHz Arbitrary Waveform Generators

Distributed by:



**Electro Systems
Associates**

www.esaindia.com

**WaveJet™
300A Oscilloscope**
100 MHz-500 MHz



4215, J.K. Complex, First Main, Subramanyanagar, P. O. Box 2139,
Bangalore-560021 Phone: +91-80-23577924 Fax: +91-80-23475615
Email: sales@esaindia.com

Chennai: 044-24851511, Delhi: 011-22012942, Hyderabad: 040-23063346, Pune: 020-25653315