



.....a total solution for
Educational Lab Trainers



8085 Trainer Kit
(LED / LCD Ver.)



8086 Trainer Kit
(LED / LCD Ver.)



8051 Trainer Kit
(LED / LCD Ver.)



Universal Embedded Kit
(8951/PIC/ARM/AVR)



PIC Trainer Kit
(PIC16F877A/18F452)



Universal VLSI Kit
(CPLD/FPGA)



Bread Board Kit
(Digital / Analog)



Communication Kit
(Digital / Analog)



Fiber Optics Kit
(Basic / Advance)



Instrumentation Kit



Protocol Trainer Kit
(Serial/Parallel/LAN)



Antenna Trainer Kit



Telephone Trainer Kit
EPABX Trainer Kit



Digital IC Tester
Linear IC Tester
Universal IC Tester



Universal Device
Programmer

Established with the motto to manufacture products with

* High Reliability

* Competitive Price

* International Quality

* Syllabus Orientation

* Inbuilt Power Supply

* Elegant Look (Enclosed in
ABS Plastic/ Wooden Enclosure)

DEALERS ENQUIRY SOLICITED

Kitek Technologies Pvt. Ltd.

B-4, Lotus C.H.S., Near P&MC Bank, Plot No. 8, Sector-7, Airoli,
Navi Mumbai - 400 708. Tel.: 022-65116548, Telefax: 022-27694323.
Email: sales@kitektechnologies.com Website: www.kitektechnologies.com

Branch : • Delhi E-mail: delhi@kitektechnologies.com
• Nagpur E-mail: nagpur@kitektechnologies.com
• Trichy (T.N) E-mail: trichy@kitektechnologies.com
• Cochin (Kerala) E-mail: cochin@kitektechnologies.com

SWITCHING POWER SUPPLIES

- EXCELLENT PERFORMANCE FEATURES
- SINGLE & MULTIPLE OUTPUTS - 5W TO 1200W
- ADAPTOR / OPEN FRAME / ENCLOSED / DIN RAIL DESIGNS.
- PLUG IN MODULES FOR 19 INCH RACKS.



SMPS BATTERY CHARGERS

- FOR LEAD-ACID / LI-ION / NI-CD / NI-MH BATTERY
- FULLY PROTECTED AGAINST ALL FAULTS
- RATED FROM 7.5W TO 1200W



BATTERY CAPACITY TESTERS

- FOR CALCULATING AH CAPACITY OF BATTERY
- CURRENT ADJUSTABLE FROM ZERO TO MAXIMUM VALUE.
- OPTIONAL BATTERY END VOLTAGE CUTOFF
- VOLTAGE RANGE - 1.5V TO 120V & CURRENT RANGE - 20A TO 200A DC.
- DATA LOGGING & PC CONNECTIVITY OPTIONS WITH PROGRAMMING FEATURES.



DC - DC CONVERTERS

- DESIGNED FOR CONTINUOUS DUTY IN MOST CHALLENGING ENVIRONMENT.
- INPUT RANGE - 12V TO 220V DC
- OUTPUT - 5W TO 1200W IN SINGLE & MULTIPLE OUTPUTS.
- EXCELLENT PERFORMANCE FEATURES
- OPEN FRAME, ENCLOSED, DIN RAIL MOUNTED & SUITABLE FOR MOUNTING IN 19 INCH RACK SYSTEMS
- ACTIVE CURRENT SHARING AND N+1 REDUNDANCY.



Strong Design Capabilities With Over 25 Years Experience

Unmatched 3 year Warranty on Almost Entire Range

The No.1 Choice Of Many OEMS



POWERCUBE

E MAIL: info@powercube.in / powercubeindia@hotmail.com

WEB : www.powercube.in

CALL : +91 98216 33610 / FAX :- +91 250 645 0623