

POWER PACKED RESISTORS FROM



WIRE WOUND RESISTORS

HEA

Semi precision Axial type.
Power Rating : 2.5W to 17W (70°C)
Resistance Range : R025 to 70K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Low surface temperature.
• Fire retardant • Pulse type available.



HFP

Power type PCB mounting.
Power Rating : 2W to 8W (at 70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%
Features : • Low cost. • Automated assembly & wave soldering possible.
• Commercial applications.



HIA/HTA

Power Axial type.
Power Rating : 0.5W to 20W
Resistance Range : R01 to 120K
Tolerances Available : 10%, 5%, 3%, 1%
Features : • Flame retardant "Thermocoat"
• Precision power. • Pulse type available.
• Non-inductive type available.



HANS

Resistance : 5K0, 1K125, 10K, 7K5
Tolerances Available : 20%, 10%, 5%
Features : • Noise suppressor resistor to reduce RF interference.



HMV

Flat vertical mounting type.
Power Rating : 2.5W to 15W (70°C)
Resistance Range : R10 to 36K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Ceramic legs act as heat sink.
• Slim profile. • Space saver. • Pulse type available.
Available in low ohm current sense type as HMVL series.



CURRENT SENSE RESISTORS

OFSC

PCB mounting.
Power Rating : 5W / 10W (70°C)
Resistance Range : R00012 to R003
Tolerances Available : 5%, 3%, 2%, 1.5%, 1%
Features : • Silicone Coated.
• Surge / current sensing applications.
• Negligible Inductance.



OA/OP

Open Frame / Axial and PCB Mounting - Shunt Type.
Power Rating : 0.5W to 5W (70°C)
Resistance Range : R0015 to R10
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Non insulated.
• Surge current sensing applications.



OF

Open Frame PCB Mounting - Punched Out Style
Power Rating : 1W to 10W (85°C)
Resistance Range : R002 to R068
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Low TCR • Tailor-made solutions possible



RL

Alloy ribbon element in cylindrical ceramic body. Axial type.
Power Rating : 0.5W to 10W (25°C)
Resistance Range : R002 to R80
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Negligible inductance.
• Replaces Moulded type.



HI-TECH RESISTORS PVT. LTD.

AN ISO 9001:2002 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA. Tel. : +91-712-2531134, 2533269, 2553691. Fax : +91-712-2528334, 2556351. e-mail : info@htr-india.com | www.htr-india.com


Malapattur

DGS & D Rate Contract For Agilent Technologies Make Products

SRB Instruments

your technology partner...

Agilent Authorised Distributors: Established in 1989 as RV Associates, we graduated to SRB Instruments Pvt. Ltd. in November 2004. In 2008 we incorporated SRB instruments Pte. Ltd., Singapore, a 100% subsidiary. Since 2005 we are registered with DGS&D and DRDO for testing and measuring instruments of Agilent Technologies. Our Client list includes Defence, Defence production, Defence research, Industry and education.



16801A
34 Channel

Price: 6,78,568

16802A
68 Channel

Price: 8,94,614

Logic Analyser

DGS & D Rate Contract No.

LOGIC_ANALYT-4/RC - D2870000/
0510/84/0A112/1204 DT. 17/06/09

Logic Analyzer : The need for validating the dynamically evolving technology becomes stronger by the day. Whether it is the most basic signal or the most advanced serial bus, it is essential to ensure that your DUT performs up to the functional standards. A Logic Analyzer is a tool that helps you functionally validate your design, whether it is basic or niche. This device is used profusely in both the FPGA and the ASIC domains to validate the functionalities of technologies that include Low Speed Serial Buses as I2C, SPI, CAN or technologies as DDR, FSB, PCIe SATA and FBDDIMM to name a few. While an oscilloscope lets you look at the parametric characteristics of a signal, it is limited to monitor only 4 analog signals. A Logic Analyzer theoretically lets you monitor any number of signals.

We also have rate contract for E8257D (250kHz to 20GHz), EXA901D (13.6GHz and 26.5GHz) and U2000A.

Contact Details: **SRB INSTRUMENTS Pvt. Ltd.**, B-28/34 Maurya Complex, Subash Chowk, Laxmi Nagar, Delhi-110092
Ph +91 11 22413422/22427534 Fax : +91 11 22459443 Delhi: 0-9810190558, Hyderabad: 0-91779196801,
Chandigarh: 0-9501338855, Dehradun: 0-9760035771 Jammu : +91 9622087028, Bangalore: 0-9008619484,
Email : info@srb-instruments.com, rakesh@srb-instruments.com / vinod@srb-instruments.com

International Operations (100% subsidiary of SRB Instruments Pvt. Ltd.):
SRB Instruments Pte. Ltd.
120 Telok Ayer Street, Singapore 068589
Email: international_sales@srb-instruments.com