

New Products

COMMUNICATION

High-density universal gateway

MATRIX has launched a high-density exchange to serve the most critical needs of large enterprises. VYOM CCX forms the vital access link to various networks such as POTS, ISDN BRI/



PRI, GSM/3G and VoIP. Its distributed processing architecture facilitates faster call processing, wider flexibility, higher reliability and easier management. Modular architecture with dedicated resources ensures high performance and better reliability for critical applications. The DSP-based call processing architecture supports up to 256 VoIP calls.

Matrix ComSec, Vadodara

Phone: (0265) 2630555

E-mail: Mary.Thomas@Matrixcomsec.com

Web: www.matrixcomsec.com

STORAGE

32GB microSDHC card

Kingston Digital has introduced a 32GB microSDHC Class 4 card for mobile entertainment and business applications.

The card can store nearly 29,000 photos, over 6000 songs and more than 2000 minutes of



video. It is claimed to work flawlessly on the latest models of smartphones, including the HTC Evo 4G and Shadow, Motorola Droid X, RIM (BlackBerry) Bold 9000 and Samsung Instinct (SPH-M800).

The card is available with a variety of adaptors including SD and miniSD, allowing one card to be used in several devices. It also comes with a small USB reader for convenient data transfer.

Kingston Technology Liaison Office (India),

Mumbai

Fax: (022) 42230399

Phone: 42230300

E-mail: sales_india@kingston.com

Web: www.kingston.com/india

LIGHTING

Retrofit PowerLED tubelight

Binay has developed a retrofit replacement solution for fluorescent tubelights that uses high-illumination power LEDs which have a life of 50,000 to 100,000 hours.

There is no need to remove the magnetic choke. The unit can run



through the choke or directly without the choke (the starter, if any, has to be removed). The output rating is 1200 lumens. The total wattage including that of the inbuilt LED driver is 16 watts. The life is estimated at 12-15 years.

Binay Opto Electronics Pvt Ltd, Kolkata

Fax: (033) 22421493

Phone: 22429082, 22103807, 22102039

E-mail: info@binayLED.com, binay@vsnl.com

Web: www.binayLED.com

TEST & MEASUREMENT

Graphical programming software

National Instruments India has launched the latest version of its graphical programming environment for design, test, measurement and control applications. LabVIEW 2010 delivers time savings with new features such as off-the-shelf compiler technologies that execute code an average of 20 per cent faster.

LabVIEW 2010 makes getting started easier. For example, LabVIEW now provides a new hardware configuration tool that makes it possible for users to access and configure their LabVIEW real-time targets remotely via a Web browser. Other features include a smart installer that automatically detects the software associated with a serial number for faster installation and an improved instrument driver finder that offers prebuilt project examples for specific instruments.

NI Systems (India) Pvt Ltd, Bengaluru

Phone: (080) 41190000

E-mail: ni.india@ni.com

CDMA2000 1x and 1xEV-DO analysis software

Rohde & Schwarz's firmware option FSV-K83 provides the capabilities for demodulation of cdmaOne and CDMA2000 1x RTT signals from mobile stations. It provides such functionalities as code domain analysis (RHO), frequency error, power-versus-power control group, constellation diagrams and bitstream), modulator parameters (IQ offset and imbalance), spectrum emission mask with settings according to the standard, adjacent channel leakage ratio and occupied bandwidth.