

phase, multi-function smart-metering and energy-monitoring applications. Featuring a dual-channel, high-performance 16-/24-bit analogue front end (AFE), the new MCUs provide



an accurate, reliable, easy-to-use and cost-effective solution for developing meters that exceed International Electrotechnical Commission (IEC) class 0.5 performance.

The family includes 64 or 128kB Flash program memory and 4kB RAM, to enable time-of-use and multi-tariff functions, as well as a high level of peripheral integration, including an LCD driver, hardware real-time clock/calendar and a charge-time measurement unit that enables a capacitive-touch user interface.

Microchip Technology, New Delhi

Fax: (011) 51608632

Phone: 51608631

Web: www.microchip.com

LCD-TFT module with touchscreen

Rhydo Technologies has introduced a compact (8.1cm) and cost-effective 'SMART' serial display module with 4-wire touchscreen. It uses the active-matrix LCD (TFT) technology with



an embedded PICASO-SGC serial graphics controller that delivers standalone functionality to any project. Powerful graphics, text, images, animation and

that can communicate via a serial port. All screen-related functions are sent using a simple protocol via the serial interface. The serial platform allows users to develop their applications using their favourite microcontroller and software development tools.

The display module has 4.9x6.5cm² viewing area with 240x320 QVGA resolution and 65,000 true-to-life colours.

Rhydo Technologies Pvt Ltd, Cochin

Fax: (0484) 2370579

Phone: 2370444, 2371666

E-mail: sales@rhydolabz.com

Web: www.rhydolabz.com

POWER SUPPLY

Square-wave home UPS

True Power has launched Signature series of square-wave home UPS in ratings of 650VA-12V, 850VA-12V and 1500VA-24V.

The stratification and sulphation removal feature of these UPS helps



the electrolyte present in the battery to stratify and bring the battery back to its normal state. The initial charge cycle too ensures longer life of the battery as the battery remains idle for a long duration before being sold to the end user.

Gravity profile management automatically senses ageing of the battery and helps in adjusting the charging parameters according to the charge acceptance of the battery.

True Power International Ltd, Delhi

Fax: (011) 27833606

Phone: 27833603, 27833604

E-mail: info@truepower.in,

service@truepower.in

UPS with inbuilt isolation transformer

Samtek Electronics has launched JTS series of compact 1 kVA and 2 kVA

online UPS. These UPS have input power factor greater than 0.9 and their inbuilt isolation transformer protects the attached sensitive gadgets. DC bus volt-



age is 60V for the 1kVA UPS and 84V for the 2kVA UPS.

Samtek Electronics, Delhi

Telefax: (011) 22799091

Phone: 22794051, 22758219

High-performance home UPS

APC by Schneider Electric has launched a high-performance home UPS system for those who face frequent, long and frustrating power cuts.

The B1850SINE can provide pure sine-wave backup power for home electronics system like television sets, home theatre systems, stereo sets, gaming equipment as well as lights and



fans. It can provide six-eight hours of continuous power supply. This is enabled by the best-in-class battery and an intelligent staged charging feature that recharges the battery efficiently even during frequent power cuts. The UPS is generator-compatible with advanced safety features and has an onsite replacement warranty of 1.5 months on the battery and two years on the unit.

Schneider Electric India Pvt Ltd, Gurgaon

Fax: (0124) 4222036

Phone: 3940400

Web: www.schneider-electric.co.in