



SMD
ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE & PASSIVE COMPONENTS

Authorised Distributor

leaguer SMD I-Capacitors

KEXIN SMD Transistors
SMD LED SMD Diodes
SMD Capacitors

watts SMD Resistors

CHIP TRANSISTORS / CHIP DIODES / CHIP LED'S / CHIP CAPACITORS / CHIP IC'S

- CHIP RESISTORS
- CHIP RESISTOR NETWORKS
- CHIP CAPACITORS
- CHIP TANTALUM CAPACITORS
- CHIP ELECTROLYTIC CAPACITORS
- CHIP ZENERS & DIODES
- CHIP TRANSISTORS
- CHIP LED'S
- CHIP SCHOTTKY DIODES
- CHIP BRIDGE RECTIFIERS
- CHIP TRANSIENT VOLTAGE SUPPRESSORS
- CHIP IC'S
- CHIP MOSFETS
- CHIP REGULATORS
- CHIP OPTO COUPLERS
- CHIP TRIMMER CAPACITORS
- CHIP INDUCTORS
- CHIP FERRITE BEADS
- CHIP HALL SENSORS
- CHIP HI LEADS & SENSORS
- CHIP POTENTIOMETERS
- CHIP FUSES
- CHIP SWITCH
- CHIP MOV'S
- CHIP THERMISTORS
- CHIP SOLDER PASTE
- CHIP SOLDER WIRE 26 SWG.

54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road, Mumbai - 400 007, INDIA. Tel. : 91-22-3240 2444 • Mob. : 93242 11912

E-mail : smdelectro@vsnl.net

STOCKIST OF ELECTRONIC COMPONENTS

Girkitt
Electro-Components Pvt. Ltd.

International Rectifier MICROCHIP
FAIRCHILD PHILIPS
SGS-THOMSON NEC
MAXIM POWER
intel DALLAS SEMICONDUCTOR
UTC National
VISHAY COSMO HARRIS
FUJI ANALOG DEVICES

"Drug House", Bldg. 54-B, Proctor Road, Mumbai - 7, INDIA.
Pin Code - 400 907 • Tel : 2387 7777 / 2380 9888
E-mail : 93222 34370 / 93227 91112 • Fax : 91-22-2387 9335
Web : girkitt@vsnl.com • Website : www.girkitelectro.com

MOBAY CENWAY AVAILABLE

Power Packed Resistors From

WIRE WOUND RESISTORS

HSR / HSRC

Capacitor Discharge,
Wire Wound Symmetry Resistors
Power Rating : 8.25W & 11W (70°C)
Resistance Range : 10K to 70K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features :
• Stainless steel mounting terminals
for direct mounting on to capacitors.

HSVA

Ceramic Encased With
Slotless Type,
Power Rating : 4W to 17W (70°C)
Resistance Range : R04 to 82K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • Low surface temperature.
• Pulse type available.

HCA

Power Axial Type
Power Rating : 1W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • High insulation.
• Fire proof • Resistant to
aggressive solvents.
• Pulse type available.
• PCB requirements.
• Bracket acts as heat sink.

HIA

Power Axial Type,
Power Rating : 0.5W to 20W
Resistance Range : R01 to 120K
Tolerances Available : 10%, 5%, 3%, 1%
Features : • Flame retardant
• Thermocouple precision power
• Pulse type available.
• Non-inductive type available.

CURRENT SENSE RESISTORS

OA / OP

Open Frame / Axial and
PCB Mounting - Shunt Type
Power Rating : 0.5W to 5W (85°C)
Resistance Range : R002 to R10
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • Non insulated.
• Surge / current sensing applications.

OF

Open Frame
PCB Mounting -
Punched Out Style
Power Rating : 1W to 10W (85°C)
Resistance Range : R0002 to R068
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • Low TCR
• Tailor-made solutions possible

HEAL

Alloy Ribbon Element / Axial Type.
Square Profile Ceramic Tube,
Power Rating : 2.5W to 12W (70°C)
Resistance Range : R0025 to R20
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • Negligible inductance.
• Surge / current sensing applications.

OFSC

PCB Mounting.
Power Rating :
5W & 10W (70°C)
Resistance Range :
R00012 to R003
Tolerances Available :
5%, 3%, 2%, 1.5%, 1%
Features : • Silicone coated.
• Surge / current sensing applications.
• Negligible inductance.

HI-TECH RESISTORS PVT. LTD.

AN ISO/TS 16949:2002 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA,
Tel: +91-712-2531134, 2533269, 2553691
Fax : +91-712-2528334, 2556351.
e-mail : info@htr-india.com | www.htr-india.com



ISO 9001:2000 CERTIFIED COMPANY