

amplify your electronics

7" LCD Industrial Panel PC with Win CE 5

owon
India



PDS
Portable Digital Storage Oscilloscope
(25 MHz to 100 MHz Bandwidth)
8" Display with optional battery



MSO
Mixed Signal Oscilloscope
(25 MHz / 100 MHz Bandwidth)
DSO with 16 Ch. Logic Analyzer
8" Display with optional battery



New HDS-1021M
Hand Held Digital Storage Oscilloscope
(Single Channel 20 MHz Bandwidth)
3.5" TFT Screen, 3 in 1
(Oscilloscope/Dig. Multimeter/Cymometer)

MINI DV 80



Smallest Digital Video Camera

- With All in One
- DV Camera
- Pen Drive
- Web Camera
- Sound Activated Camera
- 2hrs recording
- 250hrs standby time

www.minidv80.co.cc



Trainer Kit : 8051, PIC, AVR, Cypress PSoC, ARM7
With following Interface
Character Lcd/ Graphic Lcd,
Keypad, PS2, SPI, EEPROM,
USB, ADC, DAC, I-Wire, & LED's,
UART, 7-Seg/Dot Matrix LED,
Relays, DC Motor, Stepper
Motor, Buzzer, IR Remote

Available All Types of Sensors & Modules:
Gas Sensor, Smoke Sensor, GPS Module
Pressure Sensor, Humidity/Temp. Sensor Module,
Ultrasonic Distance Sensor Module, PIR Sensor,
Acceleration sensor, Bio-Metric FingerPrint Module,
DC-DC converter(Step-up/Step-down) Power Module,
RFID Reader Module, and All kind of Sensors

AMP TRONICS
amplify your electronics

6-3-905/82, Jaffer Albagh, Sonajiguda, Hyderabad - 82,
Ph : +91 40 23320240, +91 9440122805,
www.amp-tronics.com, www.owon.co.in
E-mail : info@amp-tronics.com



CPU: ARM9, 32bit 400 Mhz processor
RAM: 64 MB Flash, 128MB SDRAM
Display: 7" wide color TFT Display with 4
wire resistive touch panel
Interface: RS232, RS485, USB, SD Card,
10/100 Ethernet, Speaker with Audio,
Keyboard & Mouse Support
Power: DC 9-12V - 8W consumption
OS : Win CE 5 provided with SDK
Size : 200 X 151 X 50mm
Weight : 516g/1.0kg with battery
Optional : Wifi / Bluetooth / 2000mA
Battery & DC Adapter



Friendly ARM 9 Boards



AT UNBELIEVABLE LOW PRICE

FEATURES

CPU: 400 Mhz Samsung 2440A ARM920T
RAM: 64 MB SDRAM, 32 bit 100 Mhz Bus
Flash: 128 MB/256 MB/1 GB NAND Flash & 2 MB NOR Flash
User Interface: 4x LEDs, Keypad, ADC, SERIAL, USB, SD Card, Ethernet,
Display Interface: 3.5" LCD / 7" LCD / VGA
Debug: 10 Pin JTAG (2.0mm) with touch screen
OS Support : Linux 2.6, Win CE 5, Win CE 6, Android
*Provides Technical & Development Support

Available Range

Mini 2440 + 3.5" LCD
Mini 2440 + 7" LCD
Mini 2440 + VGA
Micro 2440 + 3.5" LCD
Micro 2440 + 7" LCD
Micro 2440 + VGA
Camera Module
USB WIFI Module

DEALERS / DISTRIBUTORS ENQUIRIES SOLICITED

**ELECTRONICS
B2B INDUSTRY IS
NOW AT A CLICK
OF A BUTTON!**

**ELECTRONICS
BAZAAR**

launches

electronicsb2b.com



- ✓ Know about the latest product
- ✓ Know about the latest technologies & innovations
- ✓ Hook the right distributors & dealers
- ✓ Know the leading players in the industry
- ✓ Know about the manufacturing techniques & best practices
- ✓ Know about the emerging leaders & the business potentials they hold

A portal rich in news, views and articles

Log on to www.electronicbsb2b.com
and be in touch with the
Electronics B2B Fraternity 24x7