



Rugged, Reliable MOSFETs for Industrial Applications

Part Number	V_{DS} (V)	$R_{DS(on)}$ Max. $V_{GS}=10V$ (m Ω)	I_D (A)	Q_g (nC)	Package
IRFS3004	40	1.75	195	160	D ² PAK
IRFB3004	40	1.75	195	160	T0-220
IRFH5004	40	2.6	100	73	PQFN 5x6 mm
IRF7739L2	40	1	270	220	DirectFET-L8
IRFS3006-7	60	2.1	240	200	D ² PAK-7
IRFS3006	60	2.5	195	200	D ² PAK
IRFH5006	60	4.1	100	67	PQFN 5x6 mm
IRF7749L2	60	1.3	108	220	DirectFET-L8
IRFB3077	75	3.3	210	160	T0-220
IRFH5007	75	5.9	100	65	PQFN 5x6 mm
IRF7759L2	75	2.2	83	220	DirectFET-L8
IRFP4468	100	2.6	195	360	T0-247
IRFH5010	100	9	100	65	PQFN 5x6 mm
IRF7769L3	100	3.5	124	200	DirectFET-L8
IRFP4568	150	5.9	171	151	D ² PAK
IRFH5015	150	31	56	33	PQFN 5x6 mm
IRF7799L3	150	11	67	97	DirectFET-L8
IRFP4668	200	9.7	130	161	T0-247
IRFH5020	200	59	41	36	PQFN 5x6 mm
IRFP4768	250	17.5	93	180	T0-247
IRFH5025	250	100	32	37	PQFN 5x6 mm
IRF7779L4	250	38	35	110	DirectFET-L8

Features

- Low on resistance per silicon area
- Optimized for both fast switching and low gate charge
- Excellent gate, avalanche and dynamic dv/dt ruggedness

The IR Advantage

- Best die to footprint ratio
- Large range of packages
- Available from 40 V to 250 V

Applications

- DC Motor Drives
- Uninterruptible Power Supplies (UPS)
- DC-DC Converters
- Power Tools
- Electric Bikes

**Your FIRST CHOICE
for Performance**

for more information, please visit us at www.irf.com or www.irf.com.cn

**International
IOR Rectifier**
THE POWER MANAGEMENT LEADER