

JAVASCRIPT-BASED ANNUAL CALENDAR INTERFACE

■ BUKYA SRIDHAR

Every year starts with a new calendar. Calendar utility is available in PCs but most of them display one month at a time. Presented here is a program coded in JavaScript that can display 12-month calendar of any year starting from 100 AD to 999 AD at a time.

The program

The calendar is displayed by using the <table> tag of HTML. Calendar cells have been designed to accommodate dates accurately.

As shown in screenshot 1, the calendar works in two modes: manual (M) and auto (A). In manual mode, you are prompted to enter a year within 100 AD to 999 AD (refer screenshot 2). It displays the calendar of that year as per the input obtained from you. In automatic mode, the program sets the current calendar and displays the 12-month calendar of the current year on the screen.

Some of the JavaScript functions used in the program are:

Set_Cal(Month, Total_days). This function is used to set the calendar month. It takes two parameters: month and total number of days in that particular month. This function has to be declared by the user manually in the code, and all the months have to

be included in the declaration of this function. So for twelve months, we call this function twelve times. It also arranges the calendar header including

clared in this function only.



Screenshot 1: Dialogue box prompting you to enter the mode



Screenshot 2: Dialogue box prompting you to enter the year



Screenshot 3: Calendar display of the chosen year

the names of the week.

The function also calls the <table> tag and arranges the table of each row and column into seven, to make the calendar matrix (refer screenshot 3).

Modes of the calendar are also de-

Week(Name). This function is used to name the week, and is called by the Set_Cal(Month, Total_days) function for writing the names of the week.

Set(). This function checks the validity of the year so entered. It also rounds off any decimal input to make it a whole number and then displays the calendar. If the entry is a valid input, it calls the Set_Cal(Month, Total_

days) function twelve times for each month, or else alerts the user of an invalid entry of the year.

It has been successfully tested by using 'JADE CLIP'. (For details, refer to EFY July 2010 issue.) When the program is run, a dialogue box appears asking for the choice of the calendar mode. Enter the mode as desired to proceed and see the calendar on the screen.

EFY note. The source code of this article is included in this month's EFY-CD and is also available on www.efymag.com website.

CALENDAR.HTM

```
<html>
<head>
<meta http-equiv="Page-Enter" content="revealTrans(Duration=1.0, Transition=23)">
<meta http-equiv="Page-Exit" content="revealTrans(Duration=1.0, Transition=23)">
```

```
<noscript style="font-family: Foot-
light MT Light; font-size: 11pt;
color: Yellow ;"> This Application Re-
quires JavaScript Plug-in which has to
be initialized or installed. It seems
that your OS does not have the Plug-in
Installed or has been disabled by you.
Please Enable/Install the Plug-in. IF
```

```
you have the plug-in and is currently
disabled, right-click on the light
yellow bar above, Chose "Allow Blocked
Content..." and then click "Yes" from
the consecutive dialog box, you should
see the Application running, or else
install the plug-in from Internet/
Reliable Disc.</noscript>
```