



Resistors With A Global Imprint

WIRE WOUND RESISTORS

HCP

Power Type
PCB Mounting
Power Rating: 3W to 20W (70°C)
Resistance Range: R10 to 56K
Tolerances Available: 10%, 5%
Features:
• Inverter / Power Supplier applications.
• Adaptable to automated assembly.
• Choice of terminal stand-off heights.
• Choice of terminals to suit exact PCB requirements.



HMV

Flat vertical mounting type.
Power Rating: 2.5W to 15W (70°C)
Resistance Range: R10 to 36K
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features:
• Ceramic legs act as heat sink.
• Slim profile. • Space saver.
• Pulse type available.
Available in low ohm current sense type as HMVL series.



HIR / RSR

Power Rating: 40W to 500W
Resistance Range: R05 to 18R
Tolerances Available: 10% & 5%
Features:
• Used for controlling motors.
• Can withstand heavy overload surges.



VHIA

Power Rating:
0.5W to 20W (40°C)
Resistance Range: R01 to 120K
Tolerances Available:
10%, 5%, 2%, 1%
Features:
• Flame retardant
• Reduced temperature at PCB solder point.



CURRENT SENSE RESISTORS

OA / OP

Open Frame / Axial and
PCB Mounting - Shunt Type.
Power Rating: 0.5W to 5W (85°C)
Resistance Range: R002 to R10
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features:
• Non insulated.
• Surge / current sensing applications.



BR

Sim type Metal Plate/
Preformed Resistance Strip.
Power Rating: 2W to 10W (70°C)
Resistance Range: R01 to 1R2
Tolerances Available: 10%, 5%
Features:
• Radial configuration.
• Negligible inductance. • Choice of 3 different preformings available.



RL

Alloy ribbon element
in cylindrical ceramic body.
Axial type.
Power Rating: 0.5W to 10W (25°C)
Resistance Range: R002 to R00
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features:
• Negligible Inductance.
• Replaces moulded type.



OFSC

PCB mounting.
Power Rating:
5W to 10W (70°C)
Resistance Range:
R0012 to R003
Tolerances Available: 5%, 3%, 2%, 1.5%, 1%
Features:
• Silicone Coated. • Surge / current sensing applications. • Negligible inductance.



**HI-TECH
RESISTORS
PVT. LTD.**
AN ISO 9001:2002 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA.
Tel: +91-712-2531134, 2533269, 2553691. Fax: +91-712-2528334, 2556351.
e-mail: info@htr-india.com | www.htr-india.com

COMPETITIVE

SMD ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE & PASSIVE COMPONENTS

Authorised Distributor

Teaguer SMD E-Capacitors

KEXIN SMD Transistors, SMD LDR SMD Diodes, SMD Capacitors

walfts SMD Inductors

CHIP TRANSISTORS / CHIP DIODES / CHIP LED'S / CHIP CAPACITORS / CHIP IC's

- CHIP RESISTORS
- CHIP BRIDGE RECTIFIERS
- CHIP FERRITE BEADS
- CHIP RESISTOR NETWORKS
- CHIP TRANSIENT VOLTAGE SUPPRESSORS
- CHIP HALL SENSORS
- CHIP CAPACITORS
- CHIP IC'S
- CHIP IN LEADS & SENSORS
- CHIP TANTALUM CAPACITORS
- CHIP ELECTROLYTIC CAPACITORS
- CHIP MOSFETS
- CHIP POTENTIOMETERS
- CHIP ZENERS & DIODES
- CHIP REGULATORS
- CHIP FUSES
- CHIP TRANSISTORS
- CHIP OPTO COUPLERS
- CHIP SWITCH
- CHIP LED'S
- CHIP TRIMMER CAPACITORS
- CHIP MOV'S
- CHIP SCHOTTKY DIODES
- CHIP INDUCTORS
- CHIP THERMISTORS
- CHIP SOLDER PASTE
- CHIP WIRE 28 SWG.

PHILIPS **int** **ICR** **NEC** **ST** **ROTHOM**

KEMET **Panasonic** **HITACHI** **ROHM** **TDK**

Infineon **ST** **ROTHOM** **Infineon** **ST** **ROTHOM**

54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road, Mumbai - 400 007, INDIA. Tel.: 91-22-3240 2444 • Mob.: 93242 11912

E-mail: smdelectro@vsnl.net

STOCKIST OF ELECTRONIC COMPONENTS

Cirkut

Cirkut Electro-Components Pvt. Ltd.

International **LED Rectifier** **MICROCHIP** **PHILIPS** **SGS-THOMSON** **NEC** **MAXIM** **POWER** **int** **DALLAS** **SEMICONDUCTOR** **UTC** **National** **semiconductor** **VISHAY** **COSMO** **HARRIS** **Ce** **FUJI** **ANALOG DEVICES**

"Drug House", Bldg. 54-B, Proctor Road, Mumbai - 7, INDIA.
Pin Code: 400 007 • Tel: 2387 7777 / 2340 8888
Mob.: 93222 34370 / 93222 81112 • Fax: 91-22-2387 9335
E-mail: cirkut@vsnl.com • Website: www.cirkutelectro.com

MOOVAT CEMENT AVAILABLE