

toring when entering into confined areas like manholes, welding-gas-purity checking, etc.

Subtronics (India) Pvt Ltd, Mumbai

Telefax: (022) 24303047

Phone: 24224461

E-mail: service@subtronicsindia.com

Web: www.subtronicsindia.com

TOOLS & EQUIPMENT

Portable labeller

Brady has introduced a versatile portable label printer (BMP 71) that has a full keypad and large screen. The printer works with more than 30 materials or variations thereof, providing more than 400 different label options. It offers the precision and versatility of a large, desktop printer in a compact, portable unit that can be carried on the jobsite.



The printer is designed to create work-

place safety labels, wire and cable markers, patch panel labels, pipe-markers, visual workplace labels, bar-code labels, and facility and asset ID labels, among other labels related to the maintenance, repair and operations market.

Brady Company India Pvt Ltd, Bengaluru

Phone: (080) 66582900

E-mail: feedback_india@ap.bradycorp.com

Battery chargers

GlacialTech Inc. has introduced a series of mini chargers for batteries generally installed in hand tools (electric



screwdrivers), household appliances (vacuum cleaners) and gardening tools (lawn mowers).

The chargers incorporate an intelligent microcontroller to monitor and supervise the entire charging process. The three-stage charging procedure implemented in the ML30 series is suitable for charging lead-acid batter-

ies. The two-stage charging procedure implemented in the MM30 and MF30 series is suitable for charging lithium-manganese dioxide and lithium-iron phosphate batteries. The charging time is well controlled to prevent batteries from overcharging and over-heating.

Acro Engineering, New Delhi

Phone: (011) 40525645

Delta-star converter module for energy-saving

Energy-saving Delstar converter module from Vijay Energy Products can be used with Star Delta starters to



save energy when the motor is partially or cyclically loaded. When the input power to the motor is lower than 50 per cent, the motor is operated in star mode to save energy. When the load goes up, the motor is operated in delta mode. Changeover from delta to star and star to delta is automatic.

The savings will be around 50 per cent at very low loads and around 20 per cent at 40 to 50 per cent load. Motor protection facilities are also provided. Options include digital indication of operating current and hour meter.

Vijay Energy Products Pvt Ltd, Velacheri

Phone: (044) 22593824

E-mail: saveenergy@vijayenergy.com

Web: www.vijayenergy.com

COMPONENTS

Mixed-signal front-end ICs

Analog Devices, Inc. (ADI) has introduced 12-bit and 10-bit mixed-signal front-ends that reduce power and board space for wireless infrastructure and portable radio equipment developers. The ICs use 40 per cent less power and 25 per cent less printed-circuit board area than competing devices without sacrificing performance. These are especially effective for cost-sensitive wireless equipment, such as femtocell and picocell base stations

that require highly integrated dual transmit-and-receive functions.

The ICs integrate two analogue-to-digital converter channels with sample rates up to 100 MSPS (mega samples per second) and two digital-to-analogue converter channels with sample rates up to 170 MSPS. These enable up to 10 dB better ACLR (adjacent-channel leakage ratio) performance than competing devices, easing design and filtering requirements while consuming less power.

Analog Devices India Pvt Ltd, Bengaluru

Fax: (080) 25216452

Phone: 41194300

E-mail: india.custserv@analog.com

8-bit microcontrollers

Fujitsu Semiconductor Asia has developed a new series under its F2MC-8FX family of high-performance 8-bit microcontrollers with embedded flash memory. The 32-pin MB95430H series includes six products with built-in analogue comparator and operational amplifier. These microcontrollers are targeted for use in home appliances and industrial equipment.

In addition to its primary function as the main microcontroller unit, the MB95430H series is also suitable as a sub-controller when current system configuration functions are insufficient, due to the availability of high-current



protection and various composite timer communication functions.

This series also employs a one-wire on-chip debug module that uses only one pin on the microcontroller for debugging, thus facilitating easier and faster product development.

Fujitsu Microelectronics Asia Pte Ltd,

Bengaluru

Fax: (080) 28416660

Phone: 28419990