

Digital Panel Meters

Nothing Hi-tech but time tested conventional Technology



DELTRONIK ENGINEERS

1st Floor, Bhatnagar Motor Market, Kashmere Gate, Delhi 110006
Ph: 011-23925994, 23913624, Fax: +91 11 43081647; E-mail: deltronik@gmail.com

Engineering Prototype Kits
Surface Mount Crystals
Chip Ferrite beads
Chip Inductors
Chip Tantulum Capacitors
Chip Transistors

Chip Capacitors

If you are looking for original Quality
Product wide range Competitive price
fastest delivery outstanding
services Most Reliable source for
SURFACE MOUNTABLE ELECTRONICS COMPONENTS
offered by

SMEC

APPROVALS
OUR CHIP RESISTORS, CHIP CAPACITORS &
TANTALUM CHIP CAPACITORS
ARE APPROVED BY ITIL

OUR CHIP CAPACITORS, RESISTORS, TANTALUM
CHIP CAPACITORS, INDUCTORS & RESISTOR
NETWORKS ARE APPROVED BY C-DOT.

Dedication of its efforts in the field of surface Mount
Technology by offering Quality Product supplying in widest
Range for Telecommunication Equipments, Office
Automation, Hybrid, defence equipments, computer & much
more with customer need, Quality, Price & delivery taken in to
highest consideration.

SMEC Electronics India Pvt. Ltd.,

Plot No. A-3, GIDC Electronics Estate,
Sector-25, Gandhinagar-382016, Gujarat, India.
Ph: (079) 23287503/04 Fax: (079) 23287505

E-mail: nitin@smec-inc.com E-mail: smecindia@bsnl.in

Ask for New Detailed Product Catalogue

Zener Diodes Diodes Melf Resistors



ISO 9001:2008 CERTIFIED

Resistors Aluminum Housed

Range: 0.1 ohms - 100K ohms
Power: 5W - 1000 W
Tolerance: ±5%



Dynamic Breaking Resistor

Range: E1 - 100 K
Power: 40 W - 10000 W
Tolerance: ±5%



Rheostat (Open / Covered / L.S.M)

Range: 0.5 ohms - 10000 ohms
Power: 0.1 Amp - 200 Amp



Potentiometer (Single / Gang Type)

Range: 1 ohms - 10K ohms
Power: 25 W - 1000 W
Tolerance: ±5%



Industrial Loads
Range: 1KW - 300KW



Low Ohmic Power Resistors
Open Frame Axial & PCB Mounting
Range: 0.001 - 1 ohms Power: 0.5 W - 3 W
Tolerance: ±5%, ±2%, ±1%



Resistors Adjustable / Fixed
(Silicone Coated)
Range: E 001 - 500 K Power: 0.5 W - 5000 W
Tolerance: ±5%, ±2%, ±1%



Resistors Ceramic Encased
Range: E 001 - 100 K
Power: 2 W - 50 W
Tolerance: ±5%

STEAD ELECTRONICS (INDIA) PVT. LTD.

Sales Office: 1681/20, Mangal Market, Bhagirath Palace, Delhi-110006

Ph: 23865929, 23862576 Fax: 011-23867465

Regd. Office: 17 U.A. Jawahar Nagar, Delhi-7

e-mail: sales@steadresistors.com visit at www.steadresistors.com

For Servo Voltage Stabilizer Manufacturers

microServo Voltage Controller

AC Synchronous Servo Motor



FEATURES

- I ndigenous design
- M easures and displays output voltage, input voltage, output current, frequency
- I nbuilt driver for AC synchronous servo motor
- A uto trip for under voltage, over voltage and over load with time delay
- A uto/Manual alarm
- F ully programmable with 2-level password protection
- U ser programmable parameters: under voltage, over voltage, over load, time delay, output voltage, sensitivity, CT ratio.



FEATURES

- P ermanent magnet AC Motors.
- N o winding on Rotor.
- R apid start, stop, reverse characteristics.
- C onstant speed of 90 rpm at 50 Hz.
- Gearing possible for reduced speeds.
- S uits in overload protection.
- S wiving and Operating currents identical.
- M agnetically rotor can be locked by DC applying.
- A luminum cast body with steel shaft.



For further information, visit: www.aeeindia.com

APPLIED ELECTRICALS & ELECTRONICS

4367/4, Ansari Road, Darya Ganj, New Delhi - 110002 (INDIA)

Tel: 011-23271468, Mobile: 9711811305, E-mail: info@aeeindia.com

DEALERS
ENQUIRY
SOLICITED