

Reach for your SiTAR_A!



Introducing the Texas Instruments Sitara™ ARM Microprocessor product family



- Starting at sub \$5 and with performance over 1GHz (2000DMIPS)
- Large portfolio of package compatible parts with different performance and peripheral options enabling leverage of software across diverse applications.
- Operating systems such as Linux, Android, Windows CE directly supported by TI. Support for industry leading RTOS like VxWorks, QNX, ThreadX, Integrity, etc are also available.
- Unique capability to build custom communication interfaces like Profibus, Additional UARTs, Smartcards, HDLC, etc.

Sitara features:

- Cortex-A8 and ARM9 processors
- High-performance 3-D graphics accelerator
- Key peripheral integration
- Flexibility of interfaces via PRU
- Robust display options
- Optimized for low-power applications
- Linux and Windows Embedded CE baseports

Highly integrated peripheral set includes:


- DDR2 support to reduce the overall cost of system memory
- Integrated CAN controller to support the increasing use of CAN for local control of sensors and controllers
- Connectivity options with high-speed USB 2.0 On-The-Go (OTG) with built-in PHY to conserve board space and a 10/100 EMAC for network communications and control of industrial devices, including remote rebooting, reducing the need for technicians to physically monitor and service devices
- 3.3-V and 1.8-V I/O eliminates the need for level shifters and lowers costs to help designers with tight budgets
- Display subsystem with picture-in-picture, color space conversion, rotation and resizing support provides flexibility to connect to an LCD display for vibrant, crisp and high-resolution images
- For more information on AM35x processors, visit www.ti.com/am35x

Targeted applications:

- Automation and control
- Human machine interface
- Medical
- Portable data terminals
- Industrial automation
- Connected displays
- Consumer goods

AM35x: Cortex-A8 processors

- 600-MHz ARM Cortex-A8 core provides 1200 Dhrystone million instructions per second (MIPS)
- PowerVR™ SGX graphics engine (AM3517 MPU only)
 - Capable of processing up to 10 Mpolygons/sec
 - OpenGL® ES 2.0
- Sub-one-watt power consumption eliminates the need for heat sinks and fans so industrial developers can design silent and air-tight enclosed solutions



▲ AM3517 processor block diagram