



FEEDBACK

YOUR SUGGESTIONS

CHIP-LEVEL SERVICING

I am one of the oldest subscribers to EFY and an electronics experimenter. The market is full of books on software, programming and the like. However, good, informative and knowledgeable books/articles on chip-level servicing of PC motherboards for the benefit of electronics hobbyists/experimenters are not readily available. I request you to carry a series of articles on this relevant topic.

A. Carvalho

Through email

3D PRINTER

I am an electronics enthusiast. I request you to publish a project on Arduino based CNC machine, XY-plotter or 3D printer.

Surajit Paul

Through email

ZIGBEE PROJECT

I am an electronics student as well as a hobbyist doing a project on transmission of three different signals to a computer using ZigBee. I request you to publish relevant articles as soon as possible.

Navratan Lal Gupta

Through email

EFY. Thanks! We will keep the above suggestions in mind while selecting material for coming issues.

THINGS YOU WANTED TO KNOW

In 'Things You Wanted To Know' Q&A section of February issue, the answer to Q1 is not fully correct. If you have a 60Hz-operated device, you just need a frequency-converter circuit to convert 60Hz to 50Hz. You should also give

the design for a frequency-converter circuit and details regarding its usage.

Shatrajit Soraisam

Through email

Corrections

In February issue, in Test & Measurement article, Oscilloscopes Available in The Market table, an OWON oscilloscope has been listed. This is not sold by the firm in India.

In Buyer's Guide article under Benchtop Power Supplies table, a MASTECH power supply has been listed that was discontinued around three years ago.

Mr Kwatra

MD, MetroQ

In EFY+DVD section published in February issue, 634-bit mentioned under Tizen SDK should be read as 64-bit.

Dinesh Kumar

Through email

On the cover page of February issue, under Top-5 Do-It-Yourself, in the 'Plus-Minus 5V Supply from 12V Battery' title, it should be 9V battery instead of 12V battery.

Roy Verghese

Through email

'Spot An Error' AWARD Winners

In 'Diabeto: A 360-degree Diabetes-Management Solution' article published in February issue, under 'Flexibility offered by this little birdie takes you by surprise', the full form of API is incorrectly mentioned as application peripheral interface instead of application programming interface.

Siddharth Kaul

In 'RGB Colour Generator' DIY article published in February issue, RGB1 shown in the schematic (Fig. 2) is wrong. It should be a common-anode type.

Tanmay Dasgupta

EFY. For conversion of 50Hz AC mains to 60Hz AC mains, it is not sufficient to convert frequency (50Hz to 60Hz) only. A 50Hz to 60Hz frequency-converter-cum-power converter will suffice. Normally, we do not provide the whole design including circuit, source code, etc in Q&A section due to space limitation.

We highly appreciate your feedback and look forward to hearing from you in future, too.

❑ In 'Things You Wanted To Know' Q&A section of January issue, under Q4, it says ATmega8 cannot be used in Arduino Uno board. This is wrong. Earlier, Arduino board used ATmega8 as the microcontroller. It can still use ATmega8 with appropriate bootloader. Of course, ATmega16 is a 40-pin microcontroller so it cannot be used.

Pramod Kumar

Through email

PLUS-MINUS 5V SUPPLY

In 'Plus-Minus 5V Supply From 9V Battery' DIY article published in February issue, 7805 used in the circuit is a popular 5V regulator. Its pins (1 and 3) should be corrected as input and output, respectively.

Abhijit Dasgupta

Through email

The author A. Samiuddhin replies: IC 7805 is a normal voltage regulator that comes in TO-220 package. 78L05 used in the circuit is a low-power 5V regulator that comes in TO-92 package and its pin connection shown is correct. Hence, no correction is required in the circuit.