

NEW PRODUCTS

MAKE IN INDIA

COMPONENTS

Intelligent power devices

Renesas Electronics has announced six new intelligent power devices for automotive motor and heater-control applications. The devices provide an extremely-reliable, high-performance solution compared with mechanical relays that switch the current flow on and off in electronic control units.

Key features are:

1. Low on-resistance for reduced loss and high reliability
2. Guaranteed on-resistance characteristics at low power supply voltages and built-in diagnostic functions
3. Excellent break-down tolerance

Renesas Electronics Corp.
www.renesas.com

Transceiver

Industrial systems designers now have a robust IO-Link dual-channel transceiver that dissipates lowest heat in the smallest package with MAX14827 from Maxim Integrated. Key advantages of the product are:

1. Lower on-resistance of 2.5-ohm r_{on} (typical) saves more than 50 per cent power dissipation
2. Tiny WLP package saves 60 per cent space
3. Robust 65V Abs maximum enables flexible TVS protection selection
4. High integration and configurability reduce SKUs with selectable PP, NPN and PNP output

Maxim Integrated
www.maximintegrated.com



Encoder splitter

Some features of this product are:

1. Input signals 4V DC - 10V DC/10V DC - 24V DC and HTL/TTL selectable by jumpers
2. Push pull/open collector (transistor) (HTL/TTL) outputs
3. Supply voltage 24V DC at 1A
4. Output pulse voltage 3.0V DC - 12V DC adjustable or 24V DC as per requirement
5. Each output can drive 100mA load
6. DIN-rail mountable/housed in an IP65 polycarbonate enclosure



Q-Log Controls and Systems
www.qlogcontrols.com

Secure microcontrollers

The 150-250 million connected cars expected on our roads by 2020 will be kept safe by chips like the latest secure microcontrollers from STMicroelectronics. The microcontrollers (ST32G512A and ST33G1M2A) provide this protection by leveraging the company's secure-technology know-how, and are qualified to the stringent automotive quality standard AEC-Q100.

STMicroelectronics
www.st.com

Polarised appliance inlets

The inlets ensure the position of live contact from the main socket into the appliance when cordsets with polarised main plugs are




used, for example, NEMA or UK plugs. However, these cordsets must be equipped with polarised connectors C7p. The polarised inlets can also be used with common C7 connectors, however, polarisation is not ensured.

Type 2577 is designed for screw-on mounting, whereas type 2579 is for snap-in mounting.

SCHURTER Electronics India Pvt Ltd
www.SCHURTER.co.in

Quad SPI FRAM

Fujitsu Electronics has announced the development of MB85RQ4ML, its new FRAM product with 4Mbit of memory, which represents the highest density in the non-volatile RAM market with a quad SPI interface. This product operates with a 1.8V single power supply, using a quad SPI interface with four I/O pins, and can achieve data transfer rate of 54MB per second. Its high-speed operation and non-volatile memory make it ideal for use in networking, RAID controller and industrial-computing fields.



Fujitsu Electronics Pacific Asia Ltd
www.fujitsu.com

I/O controllers

Microchip Technology has announced the new SCH322X family of I/O controllers customised to the needs of industrial and embedded computing designers. This next-generation product family features smaller packages and long product lifecycles, and allows for more cost-effective industrial and embedded applications. SCH322X is available in both commercial and industrial operating temperature versions.

Microchip Technology Inc.
www.microchip.com