

its STM32 microcontrollers.

STM32 USB Type-C and PD Mid-levelware Stack is compliant with USB



Type-C 1.2 and USB PD 2.0 specifications, enabling customers to rapidly deploy this new technology in their end-products, exploiting the rich feature set of the company's STM32 ARM Cortex-M based microcontrollers.

technology in their end-products, exploiting the rich feature set of the company's STM32 ARM Cortex-M based microcontrollers.

STMicroelectronics Pvt Ltd
www.st.com

Retimer

Texas Instruments has introduced three high-performance retimers that enable an extended signal range



over long traces, connectors and cables without degradation of signal integrity.

The devices expand the company's high-performance retimer portfolio, and support flexible, cost-optimised system design, enabling designers to speed their products to market while maintaining optimal performance. With up to 60 per cent lower power consumption than competitive devices and the widest temperature range from -40°C to 85°C, the retimers enable robust video and camera signal quality in equipment such as HD TVs and mobile devices.

Texas Instruments Inc.
www.ti.com

Fuse

SCHURTER's SHT 6.3 × 32 fuse provides higher voltage over-current and short-circuit protection up to 1500A @ 500V AC and 400V DC in a compact package size 6.3mm × 32mm.

The 400V DC rating provides primary protection in DC power systems for intelligent buildings, telecom

centres, server farms and related peripheral systems. The combined



AC and DC voltage ratings along with a detailed listing of breaking capacity ratings and

other precisely-defined performance specifications, offer a highly-reliable fuse approved for use in both AC or DC power applications.

SCHURTER Electronics (India) Pvt Ltd
www.SCHURTER.co.in

Monolithic ceramic capacitor

Murata Manufacturing has developed the world's first 05025M size (0.5mm × 0.25mm × 0.25 mm) mono-




lithic ceramic capacitor with a capacitance value of 1µF (X5R characteristics,

6.3V rated voltage). 05025M size cuts component volume ratio by approximately half, achieving the world's smallest component volume for a monolithic ceramic capacitor of the same characteristics.

Murata Manufacturing Co. Ltd
www.murata.com

Switching regulator

RECOM expands its low-cost, highly-efficient R-78E switching regulator series with modules featuring 9V, 12V and 15V output voltages. This series is designed to offer all advantages of a standard



switching regulator (high efficiency, wide input range and accurate output voltage regulation) at a lower cost.

The modules are equipped with short-circuit protection. Measuring

only 11.6mm × 8.5mm × 10.4mm, these save valuable board space, and with efficiency up to 95 per cent, these do not require a heat-sink.

RECOM Power GmbH
www.recom-power.com

DC/DC converter

Mornsun has introduced a DC/DC converter, PVxx-29Bxx series, to address the needs of 1500V DC photovoltaic systems. This series of DC/DC converters accepts a wide input range from 200V DC to 1500V DC, providing standard output voltages of 24V, 12V and 5V to power monitoring and control circuits in the system.

PVxx-29Bxx simplifies the wiring design, reducing the cost of system manufacturing and maintenance when compared with AC power or battery power.

Mornsun Guangzhou Science & Technology Co. Ltd
www.mornsun-power.com

PWM controller

BP3319MB is a high-precision primary-side regulation PWM controller with single-stage active PFC, especially designed for universal input offline flyback or buck-boost constant current LED lighting. The controller with on-chip PFC circuit achieves high power factor and low THD.

BP3319MB adopts proprietary primary-side current-sensing scheme. It can precisely control LED current without secondary-side sense and feedback circuits. The system size and cost are optimised, as well as system reliability.

Regency Semiconductors Pvt Ltd
www.regencysemiconductors.in

GSM/GPRS module

InkOcean has launched a new GSM/GPRS module, named A6, manufactured by AI Thinker, which measures 22.8mm × 16.8mm × 2.5mm