

CALIBRATORS

Complies with IEC1010

(safety standard issued by International Electrician Committee)



An ISO 9001:2003 Company

FEATURES :

- * Basic Accuracy : $\pm 0.05\%$
- * Display : 5 Digit LCD display.
- * Operating Temperature Range : $0 \sim 50^{\circ}\text{C}$.
Humidity range : $\leq 80\%$ RH
- * Power : 1.5V x 2 alkaline batteries.
- * Storage Temperature Range : $\leq -10^{\circ}\text{C} \sim 55^{\circ}\text{C}$
Humidity range : $\leq 90\%$ RH
- * Max. Allowable Voltage : 30V.
- * Power Consumption : about 50m / 3V.

"KUSAM-MECO"
INVITES YOU TO SEE THE LATEST
RANGE OF PRODUCTS AT:
AUTOMATION EXPO2016
22nd - 25th AUGUST 2016
BOMBAY EXHIBITION CENTRE,
GOREGAON-E, MUMBAI.
EMA ZONE HALL NO 1 STALL NO. M-47

TEMPERATURE CALIBRATOR (DCV, OHMS, TC, RTD) KM-CAL-801



- * DC Voltage range :
100mV & 1000mV
- * Ohms range : 400 Ω & 4000 Ω
- * Thermocouple : R, S, B, E, K, J, T & N
- * Thermo-Resistance :
Pt100 to Pt1000 & Cu10 to Cu50

THERMOCOUPLE CALIBRATOR SOURCE / SINK (DCV, TC) KM-CAL-802



- * DC Voltage range : 100mV & 1V
- * Thermocouple : R, S, B, E, K, J, T & N

LOOP CALIBRATOR SOURCE / SINK (DCA, DCV) KM-CAL-805



- * Display : 5 Digit LCD Display
- * DC Current range : 20mA
- * Loop Current range : 20mA
- * Voltage range : 28V
- * Loop Power : 24V

G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400015. India.
Tel. : 2412 4540, 2418 1649, 2775 0662 Fax : (022) 2414 9659, 27751612 E-mail : kusam_meco@vsnl.net