

Advanced DL 3CC CA 4x4 MIMO 256QAM mobiles are supported with no restrictions on frequency and signal bandwidth combinations.

Anritsu India Pvt Ltd
www.anritsu.com

COMPONENTS

DC/DC converters

Mornsun has developed new 50V DC and 60V DC DC/DC converter series, B05xxLD-1WR2 and B05xxLS-1WR2, specialised for BMS. These aim to reduce energy consumption of lithium battery packs and extend battery mileage. The series offers stable 50V DC or 60V DC output, ensuring the accuracy of monitored chip, meet the requirements of EMI CISPR25 class 3 standard and electrostatic discharge of ISO 10605 ± 8 kV, and have high reliability.



Mornsun Guangzhou Science & Technology Co. Ltd
www.mornsun-power.com

Appliance coupler

SCHURTER presents a waterproof IEC appliance inlet type 4761 and rewirable cord connector type 4762. The appliance coupler is perfect for supplying power to appliances used in harsh environments such as industrial, marine or laboratories.

The push/pull locking system of the connector set provides a strong reliable connection; it also features a break-away cable in the event of overload stress. The connector style is similar to the international standards of IEC and UL/CSA 60320, but is distinguished by a special arrangement

of contacts, so as not to interchange with conventional power cords. This ensures maximum power applied, IP protection and cord retention.

SCHURTER Electronics (India) Pvt Ltd
www.SCHURTER.co.in

Octal high-side switch, driver

Designers of industrial controllers can safely drive and demagnetise any inductive load for Industry 4.0 applications with MAX14913 octal high-side switch and driver from Maxim Integrated Products. With a unique safe-demagnetising clamp on each output, it easily and reliably interfaces low-voltage digital signals to 24V output-control lines.

Using its safe demagnetisation feature, MAX14913 can discharge and demagnetise any inductive load safely via its integrated clamps.

Maxim Integrated Products Inc.
www.maximintegrated.com

Microcontrollers

Microchip Technology has released a new generation of 8-bit tinyAVR mi-



crocontrollers. The four new devices range from 14 to 24 pins and 4kB to 8kB of flash, and are the first tinyAVR microcontrollers to feature core independent peripherals. These are supported by START, an innovative online tool for intuitive, graphical configuration of embedded software projects.

Microchip Technology Inc.
www.microchip.com

MISCELLANEOUS

R-Car starter kits

To accelerate the development of increasingly-complex and large-scale

automotive computing systems for the autonomous-driving era, Renesas Electronics has announced two third-generation R-Car starter kits that make the development environment more accessible to automotive software development engineers.



The kits simplify the development of the automotive Linux environment, allowing software engineers to devote their full attention to the development of highly-specialised and sophisticated software. These combine powerful computing performance and scalability so that these can be used for a wide range of computing applications.

Renesas Electronics India
www.renesas.com

Rosin flux

MG Chemicals' new rosin-activated flux is made from pure white water gum rosin, a unique solvent system and very effective activators. Its superior fluxing ability remains constant throughout the aeration process. This rosin flux contains a foaming property that provides fast wetting action. It offers superior fluxing ability, instant wetting and good spreading capabilities. It features low surface tension, thermal stability and easy to remove residues. It displays excellent foaming properties and may be applied by dip, spray or brush methods. After soldering, the rosin residue left is non-corrosive, non-conductive, moisture and fungus resistant.

Progressive Engineers
www.progressiveengineers.co.in