



FEEDBACK

YOUR SUGGESTIONS

ARTICLE ON SENSORS

The cover page of October issue shows sensors as one of the articles. It would be great if all types of sensors are covered, including humidity, gas (various types) detectors, optical, fibre-optic, optical interrupters, magnetic, inductive, proximity, capacitive, rotary encoders, pressure, displacement/motion, ultrasonic, liquid leakage, etc.

Olfactory sensors are being developed now, and artificial taste bud sensors will also be developed soon.

Naresh Ahuja

Pune

EFY. Thanks for the feedback! Apart from temperature sensors, we have covered humidity and optical sensors in DIY section, and industrial sensors including accelerometers, gyroscopes, acoustic, flow, wireless, energy-autarky, biomedical, gas sensors and so on under Tech Focus in that issue. Tech Focus also highlights 20 exciting sensor applications for a smarter world.

We will try to cover other sensors including olfactory and taste bud sensors in one of our forthcoming issues.

Once again, thanks for the suggestions, and we look forward to hearing from you in future, too.

QUADRAPHONIC AMPLIFIER

In 'Low Cost Quadraphonic Amplifier' DIY article published in August issue, how can we prevent distortions due to excessive input signal (high amplitude) if connected to this circuit? Do the values of resistor R1 and capacitor C1 need any changes in that case?

Anirvan Kule

Kolkata

The author Petre Tzv. Petrov replies:

There are three simple solutions:

1. Use appropriate potentiometer

From electronicsforu.com

Electronics Projects

In 'Arduino Based ESP8266 Wireless Web Server' DIY article published in April issue, does the circuit have a USB or RJ45 connector?

Sanjeev Kumar Singh

EFY. USB and RJ45 connectors are not used. The circuit requires a serial COM port connector.

In 'Home Automation System Using Android' DIY article published in August issue, which source code (Arduino or .apk) is given in the project?

Venugopal

EFY. The source code given is for Arduino. Both .apk file for Android and Arduino sketch are included in the DVD and also available for free download at source.efymag.com

between 10-kilo-ohm and 50-kilo-ohm, and adjust volume control.

2. Use additional voltage divider with two simple but appropriate resistors.

3. Increase value of R1 as much as you need. Normally, you need not change the value of C1 but you can do so with an appropriate value.

In order to make changes, you should know amplitude of the input signal and internal resistance of the source.

FINGERPRINT DOOR UNLOCK SYSTEM

The design of 'Fingerprint Door Unlock System Using Arduino' DIY circuit published in January issue is wrong in two aspects. In Fig. 1, relay is driven without any driver, which is dangerous to Arduino board in case of a short-circuit and sometimes during switching condition.

In PCB layout, orientation of the LCD is incorrect. The LCD cannot be used on the PCB as shown because

Corrections

In 'GPS Distance Meter' DIY article published in November issue, in Fig. 1, SCK and MISO pins of ATmega328 should be connected to SCK and DO pins of the microSD card, respectively.

Arnav Bansal

In 'Digital Soil Moisture Meter' DIY article published in November issue, in the PCB layout (Fig. 5), emitter of BC547 is directly connected to ground instead of preset VR1 and preset VR1 is wrongly connected to +5V.

Tapán Majidra and Arnav Bansal

In 'ISRO Successfully Launches Weather Satellite INSAT-3DR' Tech News article published in October issue, on page 14, in the last paragraph, '221kg rocket' should be read as '2211kg satellite.'

Kumar S. Golla

you are using PCB relay in the middle of the board. Also, the LCD will block the use of preset VR1 for contrast control.

Kamlesh

Through email

The author Dinu D. replies:

I appreciate the reader's keen observation on my article. Since we are using a 5V relay, its coil resistance may vary according to the manufacturer. A digital pin of Arduino can safely drive almost all relays with standard coil resistance. If someone places a relay with very low coil resistance (very rare case) it may damage the controller. This damage can be avoided by using a transistor as driver for the relay. This driver is not required if this circuit is used by a hobbyist but is recommended for industrial applications.

I fully agree with you regarding the PCB layout. But I do not think this would be a big problem because you can fix it by extending the LCD display connections.