

Fig. 3: Actual-size PCB pattern of the lost plane finder




Fig. 5: Wiring diagram



Fig. 6: Author's prototype




Fig. 4: Component layout of the PCB

The preferred setup in the model aircraft suggests drilling a small hole in the model wall and attaching the system so that its sounder window is aligned with the hole. Depending

on your aircraft model's structure, the whole system can be completely exposed outside of the model, too. Author's prototype is shown in Fig. 6.

Additional notes

1. Prototype was tested with R/C lithium-polymer 2S battery (7.4V).
2. Offline test is possible by feeding servo pulses to J1 from a standard servo tester.
3. An intermittent-tone piezo buzzer (sound level 85dB to 92dB)

is better than a continuous-tone type.

4. In case of an alarm malfunction, change the value of RC components (R2-C2) so that effective delay is about 30 per cent to 40 per cent bigger than the period of inputted servo pulses.
5. For a micro-size version, try to use SMD components on a stamp-size PCB. **EFY**



T.K. Hareendran is founder and promoter of TechNode Protolabz

ONLINE PCB SPECIALIST (PROTO AND SMALL VOLUME)

DESIGN SOLUTION
Eagle® PCB Design Software

PCB STENCIL
PCB LAYOUT SERVICES

SOLDERING EQUIPMENTS
Camera Assisted Pick and Place Machine (NEW)
Reflow Oven & Stencil Printer

CONTROLLED IMPEDANCE BLIND-BURIED VIAS ENIG, TIN, LEAD FREE HAL

- PCBs up to 24 Layers
- High Frequency (RF) PCBs
- No Minimum Order Quantity
- No Set-up Charges
- Delivery 24 Hrs Onwards
- Simple and Convenient Online Quote/ Ordering/ Tracking
- 24 Hrs Online Assistance
- SMS Update Services



Circuit Systems India Ltd., B-24, GIDC Electronics Estate, Sector-25, Gandhinagar-382044, Gujarat, India
Mail: pcb@pcbpower.com | Phone: +91 7600012414/+91 7600012415

