

NEW PRODUCTS

MAKE IN INDIA

TEST & MEASUREMENT

Clamp meter

The AC/DC clamp meter CM4371/CM4373 can measure multiple functions such as current, voltage, resistance, frequency, voltage detection and DC power. It can measure DC voltage up to 1700V, send alerts for hazards with a red backlight and beeping tone.

Useful functions include:

- Automatic AC/DC detection
- Auto hold
- Inrush (rush current)
- AC voltage detection function



Hioki India Pvt Ltd
info@hioki.in, neha@hioki.in

Thermal imaging camera

FLIR Ex-Series cameras are designed for a wide range of electrical/mechanical applications with MSX enhancement by using MSX technology, so users can see the visual patterns on the thermal image to easily recognise where the issue is.

These are available with resolution of 4800 pixels to 76,800 pixels with focus-free lens, multiple imaging modes and FLIR Tool software, so you can document your work and make a report easily for further use.



FLIR Systems India Pvt Ltd
www.flir.in

Field intensity meter

Model EMF828 comes with an LCD display and over-range indication

function. It can inspect particular objects or devices that radiate low-frequency electromagnetic waves. The meter can be used for power cables, computer monitors, televisions, audio and visual, electromagnetic ovens or analogous electrical installations.



Kusam Electrical Industries Ltd
www.kusamelectrical.com

TRMS digital multimeter

153B+ TRMS is a 6000-count auto-ranging digital multimeter with LCD backlight and holster. It has voltage range up to 1000V DC and 750V AC, and current range up to 20A AC and DC. Basic accuracy for DC voltage is $\pm 1.0\% \text{rdg} + 4 \text{dgt}$, for AC voltage $\pm 1.0\% \text{rdg} + 5 \text{dgt}$, for DC current $\pm 1.0\% \text{rdg} + 2 \text{dgt}$ and for AC current $\pm 1.5\% \text{rdg} + 5 \text{dgt}$. It has special features like auto power off, diode test, audible continuity and data hold, besides measurement of resistance, capacitance, frequency and duty cycles.



Mecco Instruments Pvt Ltd
www.meccoinst.com

COMPONENTS

Fibre-optic module

The fibre-optic module, PST-850/DPM, comprises an encapsulated panel-mountable device that receives

optical power through a graded index multi-mode or single-mode glass fibre at 660nm, 850nm or 950nm and converts it into an electrical voltage



equivalent to the optical power measured in dBm. The module is specially designed to operate from an IC7106 dpm power source (9V DC). Reference voltage for IC7106 needs to be set at 2000mV.

Telenet Systems
www.telenet-systems.com

Automotive motor drivers

Texas Instruments has introduced two new automotive motor drivers that support high-performance power train applications. DRV8305-Q1, a highly-integrated three-phase brushless DC gate driver, and UCC27211A-Q1, a high-current half-bridge gate driver, improve system performance and provide design flexibility to meet a diverse range of automotive system requirements.

Texas Instruments Inc.
www.ti.com

I2C digital isolator

MAX14933 is a two-channel, 2.75kV_{RMS} I2C digital isolator utilising Maxim's proprietary process technology. It transfers digital signals between circuits with different power domains at ambient temperatures up to +125°C. It also features two bi-directional, open-drain channels for applications such as I2C, that require data to be transmitted in both directions on the same line.

Maxim Integrated
www.maximintegrated.com