



FEEDBACK

YOUR SUGGESTIONS

IoT TEMPERATURE LOGGING

The 'IoT Wi-Fi Temperature Logging' DIY article published in March issue is a very good project. Where can I get ESP8266 Wi-Fi module? Can I use a different microcontroller for this project instead of PIC?

Abhijit Kulkarni

Through email

□ In 'IoT Wi-Fi Temperature-Logging System' DIY article, a logic-level shifter module is used. I am unable to find the part number in the article. Can you please tell me the part number and its availability?

Abhijeet Kumar

Founder, QuintSpark

The author Osho Gera replies:

ESP8266 module is easily available on the Internet. Any other microcontroller can be used in the project. I have developed the same project on ATmega16.

Given below are the links to the level shifter:

www.sparkfun.com/products/11771

<http://artofcircuits.com/product/i2c-level-conversion-module-3v-5v>

You can get the basic information on the level shifter from here and even order it if you wish.

EFY. Some logic-level shifters, including the one used in this project, do not have specific part numbers.

CONFIGURABLE RS232

In 'Configurable RS232 to TTL to I2C Adaptor' DIY article published in April issue, IC2 should be 7405 instead of 7404.

Samiuddin

Through email

From electronicsforu.com

Do-It-Yourself

In 'Earth Quake Indicator Using Arduino' DIY article published in January issue, after compiling the code it shows 'EEPROMAnything.h directory doesn't exist' error message. Please help.

Shiva Kumar

EFY. EEPROMAnything.h is a library file required for compiling the code. This was missed in the accompanying DVD of the issue. It has been uploaded on source.efymag.com. You can also download the same from [Google/GitHub](https://github.com).

The author Petre Tzv Petrov replies:

Please note that there are a lot of hex inverters depending on inputs and outputs. In the mentioned project we need open-collector output and so 7405 or 7406 is used. Some other hex inverters are listed below:

- 7404 is a hex inverter with totem-pole output (not required in this project)
- 7405 is a hex inverter with open-collector output (up to 5.5V)
- 7406 is a hex inverter with open-collector output (up to 30V)
- 7414 is a hex inverter with totem-pole output and Schmitt trigger

WIRELESS CHARGING TECHNOLOGY

In 'The Evolving World of Wireless Charging Technology' article published in April issue, on page 34, under Resonant wireless charging sub-head, it is mentioned that "There are mainly two types of wireless charging: inductive and conductive," whereas the article further mentions that conductive requires a direct con-

'Spot An Error' AWARD Winners

In 'Arduino Based ESP8266 Wireless Web Server' published in April issue, IC6 was wrongly printed as MAX232 instead of MAX3232 in the component layout. In the PCB layout, top-silk outline of IC6 is transferred into the solder side shorting the tracks of IC6.

A. Samiuddin

In eStyle Buyers' Guide on 'Selecting An Appropriate Rooftop Solar System,' published in April issue, the cost of the solar panel is mentioned in ₹/kW, but it should be ₹/watt. Similar mistakes are seen throughout the paragraph.

Himanshu Tiwari

In 'Alarm Clock-cum-Temperature Indicator' DIY article in April issue, CON1 for 9V battery is mentioned in the text and Parts List table but is missing in the schematic and PCB layout. It should have been backed up by a low-cost timing reference IC like DS1307 or DS3231.

M. Hyder Hossain

In 'Alarm Clock-cum-Temperature Indicator' DIY article, LM35 specification is wrongly given as -50°C to 100°C instead of -55°C to 150°C. Also, under Circuit and working, pin 20 of Vcc is wrong. It should be Vdd (as per datasheet). Footprints of all resistors in the PCBs should be ¼W resistors.

Shatrajit S.

nection, hence it is not wireless.

Ravi Sakshena

Ahmedabad

The author S.S. Verma replies:

I have gone through my article and fully agree with the observations made by the reader. The word wireless has been used inadvertently. Under Resonant wireless charging sub-head the sentence should be read as "There are mainly two types of charging: inductive and conductive."