



These 1200V devices can achieve total switching loss characteristics; the remarkable improvement in performance is attributable in part to a very wide highly-activated field-stop layer and optimised co-pack diode.

ON Semiconductor
www.onsemi.com

CMOS opamps

STMicroelectronics has introduced the new TSX7 series of precision 16V



opamps that combine very high accuracy with a wide operating-voltage range and excellent robustness. The low input-offset voltage, common-mode rejection ratio and temperature drift eliminate any need for trimming or calibration in the assembled circuit

while ensuring consistent performance over a wide automotive-grade temperature range from -40°C to 125°C.

STMicroelectronics
www.st.com

CEE connector

SCHURTER expands its range of power-entry modules with the introduction of FMAD and FMAB CEE connectors, featuring a first-of-its-kind integrated line filter for 1- and 3-phase industrial and power distribution applications.



The integrated filter optimises suppression of conducted emissions by eliminating cables between the inlet and filter.

SCHURTER Electronics (India) Pvt Ltd
www.SCHURTER.co.in

MISCELLANEOUS

Linear luminaires

R. STAHL 6002 and 6402 series linear luminaires use the latest LED technology inside. Suitable for ceiling installation, use as pendant lights or pole-mounting, these explosion-proof devices enable particularly energy-efficient general lighting in zones 1, 21, 2 and 22. Their form factor ensures that changing over from traditional linear

luminaires with fluorescent tubes to LED light sources is an especially straightforward process.



In photometric terms, one 52W luminaire is fully equivalent to two conventional 36W fluorescent lamps. However, up to 100,000 hours of operation means these achieve a far superior service life, as well as a high luminous flux of up to 5800lm and excellent luminaire efficiency of well over 100lm per W.

R. Stahl Inc.
www.rstahl.com

Photo-imageable solder-resist ink

DH-9000 LED-368-1B is a high-class, super-white liquid photo-imageable solder-resist ink, specially designed



for roller printing and screen printing. It does not change colour during reflow process. It has a high reflecting rate, low heat-discolouration degree and excellent coverage. It is designed for production of Al based CCL and FR4 LED high-precision boards.

Binita Trading Co.
mbinita@gmail.com

**To read more stories about
manufacturing and SMT**

Log on to

www.electronicb2b**.com**

