

WE WERE
SHOCKED
WHEN CUSTOMERS
TOLD US THEY WERE
BUYING
LED LIGHTS
AT THESE PRICES!



Eveready 9W LED Bulb
Local Shop Price - ₹350
@ LEDBazaar.in - ₹279



Motion Sensing LED Bulb
Local Shop Price - ₹699
@ LEDBazaar.in - ₹699



3W Round LED Panel Light
Local Shop Price - ₹550
@ LEDBazaar.in - ₹275



Are YOU Also Thinking About Buying
LED Lights? Lowest Price Guaranteed
For Top Brands. **TRY US OUT**

LED  **Bazaar.in**

Top Brands. 5 Star Service. Chandni Chowk Prices.

Free Home Delivery Within 24 Hours in Delhi, NCR

Same Day Dispatch for Rest of India

For more details, call 08800094207, 011-40566605 or write to us at: foryou@ledbazaar.in

Note: Same day dispatch is applicable for the orders received till 4 pm. Rest will dispatch by next day.

RapidIO end-point (EP) and RapidIO switching fabric. With integrated EP within SoCs, it is possible to offer lowest latency between applications. With low-latency high-throughput packet based switching protocol, applications can be executed and partitioned across a large number of baseband computing units.

To support lowest latency, it is further possible to co-locate baseband processing units for a large number of small cells in one location. In this case, X2 interface is local to the baseband cluster. Exchange of information with deterministic delivery and lowest latency allows the baseband cluster to control data exchange between the right set of radio units and the baseband units at the right time while minimising or avoiding interference even for users located at cell boundary.

With a cluster of baseband units, it is possible to virtualise and share processing units. This allows average processing capability of computation units to meet the total capacity of a group of cells at any given time, instead of a specific cell all the time.

The technique will be used in big cities, especially in stadiums and subways, which carriers will not want to pack with base stations to handle traffic peaks. C-RANs will also help carriers share the cost of network infrastructure. In some cases, even single antenna will be shared by carriers and will have an IPsec session with data from different carriers in it. Real rollouts are more for 5G networks and define architectural requirements in hardware and software.

One of the biggest challenges is getting servers to handle real-time requirements of physical layer baseband processors. Ideally, some baseband traffic should traverse round-trip paths at milli- or even micro-second speeds. However, time constraints are still fuzzy, because it is more about user experience and the Internet experience.

At first, hybrid designs would let servers handle session- to application-layer jobs, offloading lower-level work to accelerator cards. A classic server works for the control plane but today would not handle transport functions and layer 2 and down very well. In the long term, it will presumably look for ways to integrate server and baseband functions.

Software poses several challenges because carriers will want C-RANs to use their current code. In addition, developers need to figure out how to assign various networking jobs to virtual machines and keep those machines secure. They will also have to find ways to run both general-purpose processor and accelerator codes in virtual machines. **EFY**