

NEW PRODUCTS

MAKE IN INDIA

TEST & MEASUREMENT

Network test solution

The MA8100A series TRX NEON signal mapper simplifies and reduces time required for indoor signal testing. Its automatic indoor location and path estimation feature removes conventional data recording errors caused by 'guesstimation' locations in large buildings. It can also deliver actionable data in areas not easily analysed, such as stairways and elevators, by recording and referencing measurements in 3D.

Users can initialise their location, start/stop mapping and load mapping data to the cloud for centralised access and visualisation.

Anritsu India Pvt Ltd
www.anritsu.com

Digital lux meter

Meco digital lux meter model 930P is used for measuring luminance and

the intensity of light over the range of 0 to 200,000 lux and 0 to 20,000 fc with special functions: max, min, backlight and auto power off. It can be widely used because of its portability, light weight and accuracy. It has a wide range of luminance, long battery life and is user-friendly.

Meco Instruments Pvt Ltd
www.mecoinst.com

Industrial multimeters

FLIR's DM92 and DM93 digital multimeters offer variable frequency drive filtering to help accurately analyse non-traditional sine waves and noisy signals. The DM93 also offers Bluetooth to

connect a compatible smartphone for remote viewing and sharing, and METERLiNK technology to wirelessly embed electrical readings into radiometric infrared images on compatible FLIR thermal cameras.

Their dual display shows voltage and frequency at once, besides true RMS voltage and current. The LoZ mode eliminates ghost voltage error readings caused by long wires. The powerful LED lights eliminate need for flashlight in dim lighting. Have large, easy-to-read digits, backlit display and analogue bargraph.

FLIR Systems India Pvt Ltd
www.flir.com/test

Clamp meter

Kusam-Meco has introduced true RMS AC/DC clamp meter model 9999 with in-rush current measurement. It uses high-speed digital signal processing to filter out electronic noise and captures the in-rush current.

The meter has large 27mm LCD display for easy readout. Its auto power-off feature increases battery life, can take conductor of 46.5mm dia and has crest factor ≤ 3 . It can measure AC/DC current up to 999.9A, AC/DC voltage up to 600V, resistance up to 999.9 Ω , frequency from 10Hz to 400Hz and temperature 40°C to 1200°C. It can also test diodes and continuity.

It is useful for PWM troubleshooting and measurement in noisy environments. Sufficient input protection is provided for the measurements. Oper-



ates on 9V battery and has hold, max and auto-zero facilities.

Kusam Electrical Industries Ltd
www.kusamelectrical.com

COMPONENTS

Op amps

STMicroelectronics has introduced two 36V op amps that deliver enhanced performance and ruggedness in automotive and industrial applications. The op amps feature a wide supply-voltage range, stability in challenging operating conditions and tolerance of electrostatic discharge up to 4kV.

The TSB572 and TSB611 single op amps use ST's new 40V-ready BiCMOS semiconductor process, which delivers superior GBW/Icc efficiency resulting in about five times lower supply current than standard op amps. In addition, low input-offset voltages with temperature drift below 6 μ V/°C simplify system design, eliminate any need for trimming or calibration and ensure consistent performance over -40°C to 125°C range.

The TSB572, with rail-to-rail inputs and output, has 2.5MHz gain-bandwidth (GBW) and 1.5mV maximum input-offset voltage. The op amp is stable with capacitive loads and highly resistant to phase reversal. Its 4V to 36V supply-voltage range allows reliance on specified parameters with a wide variety of power supplies. The TSB611 has 560kHz GBW and can operate from a supply voltage as low as 2.7V. It is a unity-gain-stable device with input-offset voltage of just 1mV and frugal operating current of 125 μ A (max.) at 36V.

STMicroelectronics
www.st.com

Power analogue controllers

Microchip has announced two new digitally enhanced power analogue controllers designed for LED lighting applications. The MCP19116 and MCP19117