



Each click of a dial opens a doorway to precision




2560A PRECISION DC CALIBRATOR

1. High accuracy
DC voltage: ± 50 ppm DC current: ± 70 ppm
2. High stability
DC voltage: ± 10 ppm/h DC current: ± 20 ppm/h
3. High resolution
5.5 digits, ± 120000 count display 6.5 digits, ± 1200000 count display*
4. 5 voltage ranges (100 mV, 1 V, 10 V, 100 V, 1000 V)
7 current ranges (100 μ A, 1 mA, 10 mA, 100 mA, 1 A, 10 A, 30 A)

2558A : AC VOLTAGE CURRENT STANDARD

1. High accuracy
AC voltage : ± 0.04 % AC current : ± 0.05 %
2. Wide output range
AC voltage : 1.00 mV to 1200.0 V AC current : 1.00 mA to 60.00 A
3. Wide frequency range
40 to 1000 Hz (Frequency accuracy : ± 50 ppm)



2553A PRECISION DC CALIBRATOR

1. High basic accuracy
DC Voltage: ± 75 ppm DC Current: ± 120 ppm
2. High stability and low noise
Stability: ± 15 ppm/h Noise: 2 μ Vrms
3. High resolution
5.5 digits ± 120000 count output resolution

YOKOGAWA 
Test & Measurement

Plot. No.96, Electronic City,
Hosur Road, Bangalore- 560 100

Tel: +91 80 41586396
Fax: +91 80 28528656

Email: tmi.india@in.yokogawa.com
Web: www.tmi.yokogawa.com

For more details: <http://tmi.yokogawa.com/in/products/portable-and-bench-instruments/>