

Source & Measure Units

GS200, GS610 & GS820

GS200



Fuel Cells

Photovoltaic

LED Lighting

- Voltage source up to +32 V and current source up to +200 mA
- 5 1/2-digit, 120000-count output resolution
- Voltage and current simple monitoring feature (optional)
- Programmable output up to 10,000 points
- Built-in USB mass storage device
- Channel expansion through synchronous operation

Batteries

Electronic Load

GS610



- Source and sink operation up to 110 V/3.2 A (four-quadrant operation)
- Basic accuracy: +0.02% (DC voltage generation)
- Sweep output at up to 100-μ intervals
- Comes with abundant sweep patterns (linear, logarithmic, and arbitrary)
- Stores up to 65535 points of source measure data in the internal memory
- Remote control and FTP using Web server function
- Easy file operation with the USB storage function

GS820



- Isolated 2-channel source and measurement function
- Source and measurement ranges: 7 V and 3.2 A or 18 V and 1.2 A
- Minute current ranges with 200-nA or 1-pA resolution
- Generate arbitrary waveforms consisting of up to 100,000 points at 100-μs intervals
- Channel expansion through master-slave synchronization link
- Fast test speeds
- 16-bit digital I/O (model 765602)

Components & Materials

Semiconductor

Production

www.tmi-yokogawa.com

 QUALITY ■ INNOVATION ■ FORESIGHT
 QUALITY ■ INNOVATION ■ FORESIGHT

YOKOGAWA ◆