

NEW PRODUCTS

MAKE IN INDIA

TEST & MEASUREMENT

RTD calibrator

Model KM-720 is a hand-held RTD calibrator that can source and measure from seven types of RTD devices. Its temperature accuracy is $\pm 0.2^{\circ}\text{C}$ with a 0.1°C resolution. Its resistance accuracy is $\pm 0.1\ \Omega$ with $0.1\text{-}\Omega$ resolution. The set includes a calibrator, test lead, crocodile jacks, 1.5(AAA) x 6 battery, carrying case and user manual.



Kusam Electrical Industries Ltd
www.kusamelectrical.com

IR thermometer

Key features of IR260 thermometer are:

- IR temperature range: -20°C to 400°C
- Basic accuracy: $\pm 2\%$ of reading or 2°C
- Distance to target: 12:01
- Emissivity: 0.1 to 1.00
- Built-in laser pointer
- Adjustable emissivity for better accuracy
- Programmable high/low alarm alerts



FLIR Systems India Pvt Ltd
www.flir.in

Automatic multimeter

Testo 760 digital multimeter family comprises three models for electrical measuring tasks. Function keys replace the traditional dial on all three instruments, which means easier operation and greater reliability.

Incorrect settings are now impossible, because measurement parameters are detected automatically via assignment of measuring sockets and also shown by illumination of appropriate function keys.



Testo India
www.testo.in

COMPONENTS

MOSFETs

STMicroelectronics has introduced a portfolio of TO-220 FullPAK (TO-220FP) wide-creepage power transistors, including the world's-first 1500V super-junction MOSFET in this new important arcing-resistant package.

TO-220FP is ideal for power transistors of open-frame power supplies commonly used in equipment such as television sets and PCs, which are vulnerable to surface contamination by dust and particles that can cause high-voltage arcing between transistor terminals.

STMicroelectronics Pvt Ltd
www.st.com

DC/DC converters

RECOM's new RP10-A and RP10-AW series includes a range of DC/DC converters for applications where wide input range and accurate regulation are key factors.

These can be used in a wide operating temperature range of -40°C to $+100^{\circ}\text{C}$ (derating starts at 78°C depending on the model and cooling method) and offer an efficiency of 91 per cent.

Additional features include under-voltage lockout, short-circuit, over-current and over-temperature protection. Outputs can be trimmed by ± 10 per cent to perfectly fit the needs of the load.

RECOM Power GmbH
www.recom-power.com

Power module

Product features are:

- Meets UL, CE requirements
- AC voltage input: $90\text{V} \sim 264\text{V}$
- Low ripple and low noise
- Output overload and short-circuit protection
- High efficiency, high-power density
- Meets requirements of EMC and safety test
- Low power consumption, environmental protection, no-load loss less than 0.1W
- 100 per cent load aging and testing

Rajguru Electronics
dileep@rajguruelectronics.com

Power supply control ICs

ROHM has announced the availability of isolated flyback-type DC/DC converter control ICs for inverters in high-power industrial equipment such as FA/solar inverters and power storage systems.

