

New Products

COMPONENTS

8-bit microcontrollers

Millennium Semiconductors has introduced microcontroller units (MCUs) from Fujitsu that are built on advanced Flash technologies. Majority



of these MCUs offer energy-efficient, low-power modes and are available in packages suitable to withstand automotive environments and interface with in-vehicle controller-area network and local interconnect network.

Under the 8-bit MCUs, the company offers F2MC-FX family, MB95200 series, MB95300 series and the MB95R203/MB95R203A. The MB95200 series has a variety of low-pin-count MCUs with ROM size varying from 4 kB to 60 kB. The MB95300 series is capable of three-phase waveform output that is optimal for brushless DC motor control. The MB95R203/MB95R203A are single-chip MCUs applicable as application-specific integrated circuits.

Millennium Semiconductors, Pune

Fax: (020) 27421486

Phone: 27484800, 27484900, 27484500

Web: www.millenniumsemi.com

IR receivers

Vishay Intertechnology, Inc. has broadened its optoelectronics portfolio with the introduction of a 'V' low-voltage supply option for ten of its TSOP series IR receivers.

The V series devices operate with a stable sensitivity rating at a very low supply voltage down to 2V over

a temperature range of +5°C to +85°C.

In two-cell alkaline battery applications, a typical discharge curve under a 160 mA load goes from 3V down to



2.5V after about three hours of operation. This would represent the end of life for a standard receiver operating down to 2.5V. Typically, the non-linear battery discharge curve then provides a further 13 hours of operation before reaching 2V. Thus a receiver capable of operating to 2V can extend the useful battery life by a factor of more than four.

End products for V series include small handheld battery-powered systems like digital still cameras, bidirectional remote controls and 3D goggles.

Vishay Components India Pvt Ltd, Bengaluru


Fax: (080) 25584291

Phone: 25586277

E-mail: business-asia@Vishay.com

Radial leaded capacitors

AVX Corporation has expanded its AR series of radial leaded capacitors to include AEC-Q200 qualified devices



in axial configuration. Designated the Spinguard AA series, these are claimed to be the industry's first axial leaded multi-layer ceramic ca-

pacitors to meet the latest electronic component qualification initiative for automotive applications.

The capacitors have values of 0.002 μ F, 0.01 μ F and 0.1 μ F in 50V and 100V. An operating temperature range of -55°C to +125°C makes these ideal for a variety of automotive applications.

AVX/Kyocera India liaison office, Bengaluru

Fax: (080) 41467424

Phone: 64500715

Web: www.avx.com

High-voltage battery monitor

Linear Technology has announced a second-generation high-voltage battery monitor for high-voltage, high-performance battery systems like electric vehicles.

The LTC6803 is a complete battery measuring IC that includes a 12-bit analogue-to-digital converter, a precision voltage reference, a high-voltage



input multiplexer and a serial interface. The device can measure up to twelve individual battery cells in series. Its proprietary design enables multiple LTC6803s to be stacked in series without optocouplers or isolators, permitting precision voltage monitoring of every cell in long strings of series-connected batteries.

Linear Technology Pte Ltd, Singapore

Fax: (+65) 67520108

Phone: 67532692

Web: www.linear.com