

Differential line transceiver with integrated driver

Texas Instruments (TI) has introduced an isolated half-duplex differential line transceiver with integrated transformer driver.

The ISO1176T—an isolated Profibus RS-485 transceiver—provides 2500Vrms of isolation between the line transceiver and logic-level interface to reduce risk of data corruption and damage to expensive control circuits over long transmission lines. It operates at 40 Mbps, enabling faster data transmission. Also, it supports 160 nodes, reducing the number of repeaters required and system cost.

The ISO1176T is compatible with regulators like TI's TPS76350—a low-dropout voltage regulator that offers the benefits of low-power operation and small package.

Texas Instruments India, Bengaluru

Phone: (080) 41381665

E-mail: tiasia@ti.com

Web: www.ti.com

Pulse-width modulation current-mode controllers

ON Semiconductor has expanded its portfolio of AC-DC power solutions for home electronics with introduction of



the NCP1234 and NCP1236 families of fixed-frequency pulse-width modulation (PWM) current-mode controllers.

The controllers allow high-performance offline power supplies to be designed into systems while minimising the footprint and board space area required. Utilising a high-voltage process technology, these integrate multiple features such as over-power

compensation, brownout (NCP1236 only) and ramp compensation without increasing the power dissipation or adding external components. High-voltage dynamic self-supply technology enables direct connection to the line voltage, eliminating the need for startup resistors.

Arrow Electronics India Pvt Ltd, Noida

Fax: (0120) 4535505

Phone: 4535500

Web: www.arrowasia.com

TEST & MEASUREMENT

Speed-monitoring relay

YSL Electronics has launched a speed-monitoring relay that controls output based on the current speed of the monitored system.

The SMR-1 can be interfaced to either an npn or pnp sensor to calculate the speed.



Depending on the requirement, it can be easily set to operate in over-speed or under-speed modes. Further, for each operating

mode, different time functions such as no-delay, no-delay inverse, off-delay, off-delay inverse, on-delay, on-delay inverse can be selected.

The speed measurement range is 1-9999 rpm. Based on the application, the required speed, hysteresis and other parameters can be easily set.

YSL Electronics, Bengaluru

Phone: (080) 28461413, 28566413, 28566414

E-mail: ysl-electronics@gmail.com

Web: www.yslelectronics.com

RF vector signal analyser

National Instruments (NI) has introduced a 3.6GHz RF vector signal analyser (VSA) that delivers RF performance in a cost-effective PXI form factor.

The NI PXIe-5665 can be used for spectrum and wide-band vector signal measurements over a frequency range

from 20 Hz to 3.6 GHz with analysis bandwidths up to 50 MHz. It features



low-phase noise of -129 dBc/Hz at a 10kHz offset at 800 MHz, an average noise level of

-165 dBm/Hz, a third-order intercept point of +24 dBm and absolute amplitude accuracy of ± 0.10 dB.

NI Systems (India) Pvt Ltd, Bengaluru

Phone: (080) 41190000

E-mail: ni.india@ni.com

Arbitrary waveform generator

Agilent Technologies Inc. has added a high-resolution, wide-bandwidth, 8 or 12Gsa/s modular instrument to its portfolio of arbitrary waveform generators (AWGs).

The M8190A offers 14 bits of resolution and up to 5 GHz of analogue



bandwidth per channel simultaneously, the ability to build realistic scenarios with 2 Gsa/s of waveform memory, and reduced system size, weight and footprint with compact modular AXIe AWG capability. It has a proprietary digital-to-analogue converter (DAC). Fabricated with a silicon-germanium BiCMOS process, the DAC operates at 8 Gsa/s with 14-bit resolution and at 12 Gsa/s with 12-bit resolution.

Agilent Technologies India Pvt Ltd, New Delhi

Fax: (011) 46237106

Phone: 46237134

Mains-operated LED lamp driver

STMicroelectronics has launched the first in a new family of mains-operated LED lamp drivers that will enable designers to deliver reliable and efficient LED retrofit lamps featuring primary-side current regulation.

The HVLED805 integrates an 800V avalanche-rugged MOSFET achieved