



Power Up Your LEDs

MBI6660/MBI6661

Power Switch Embedded, Driving an Array of 10-14 pieces of 1W LEDs by 52V DC Power Supply, Maximum Constant Output Current Reaches 1A

High Efficiency

Maximum efficiency reaches 97%, and the hysteretic PFM improves the efficiency at lighting loading.

Protection Upgrade

Complete protections to prevent IC from damage, (UVLO / OCP / Start-Up / Thermal Protection / LED open-/short-circuit)

Simplified Design

Only 5 external components required to simplify the circuit design and save the PCB space for cost reduction, while maintaining good performance and reliability.



Designed for High Power LED Lighting and Street Light Applications

	DC/DC Converter						
	MBI6651	MBI6652	MBI6653	MBI6654	MBI6655	MBI6660	MBI6661
Topology	Buck / Hysteretic PFM						
Max. Output Current per Channel	1A	750mA	1A	1A	1A	500mA	1A
Max. Sustaining Voltage	40V	32V	40V	40V	40V	75V	75V
Supply Voltage	9-36V	6-30V	6-36V	6-36V	6-36V	9-60V	9-60V
Switch ON Resistance (Typ.)	0.45Ω	0.45Ω	0.3Ω	0.3Ω	0.3Ω	0.3Ω	0.3Ω
Protection	Dimming Method						
	Digital						
	Analog						
	Panel Switch						
	LED Open-/Short-Circuit						
	Thermal						
	Start-Up						
	UVLO						
	OCP						
	TO252						
RoHS Compliant Package	SOP8						
Major Applications	MR11, MR16, Flood Light, PAR Light, Wall Wash Light, Emergency Lighting, Street Light, Tunnel Lighting, High Power LED Lighting						

Tel: +886-3-579-0068 • Fax: +886-3-579-8934 • Website: www.mblock.com.tw • Email: marketing@mblock.com.tw

www.lsis.biz



Leading Innovation, Creating Tomorrow



Sputtered Pattern
-Cu, Al and etc.
-Thickness: 100~500nm

Coated Ceramic
-Al2O3, AlN, SiC, Si3N4
-Thickness: 100um

Base Plate

IBP(Integrated Base Plate) Technology

Direct Ceramic Coating onto Base Plate
Plasma Sputtered Pattern

Advantages of IBP Product

Reliability

- Improved Thermal Cycle
- No Solder Fatigue b/w. Base Plate & Substrate
- CTE Match



Performance

- High Thermal Conductivity
- Low Ceramic thickness, No Solder b/w
- Base Plate & Substrate
- High Current Capability
- Thick Pattern
- High Thermal Conducting to Heat Sink
- Flatted Base Plate

Application

- Industrial Motor Drives
- Welding Machines
- UPS/EPSS
- Induction Heating



Full Bridge Modules IGBT

It offers a package type of SISPM1 and it covers the different current range from 50A to 100A (@Tc > 80°C) at 600V.

Features

Operation frequency - up to 40 kHz

Application

- Welding Machine
- UPS
- SMPS
- PV Inverter



Full Bridge Modules MOSFET

It offers a package type of SISPM1 and it covers the different current range from 30A to 60A (@Tc = 25°C) at 500V and 900V.

Features

Operation frequency - up to 100kHz

Application

- UPS
- SMPS
- Welding Machine



Industrial Systems

Authorized Distributor of LSIS in India



MILLENNIUM SEMICONDUCTORS

Corporate Office: 17/18/19/ 2nd Floor, Mahalaxmi Heights, Mumbai-Pune Road, Pimpri, Pune-411018, Maharashtra, INDIA

Cell : +91- 9552594615, Tel: +91-20-27484800/27484900/27485000,

Fax : +91-20-27421486, Email: sunil@millenniumsemi.com

www.millenniumsemi.com