

operates across industrial temperature range of -40°C to 125°C.

The amplifier has 90dB common-mode rejection ratio (CMRR) when operating in direct current mode and 80dB CMRR in alternating current mode. The AD8429 is available in a 4×5mm² plastic small outline, narrow body package.

Analog Devices India Pvt Ltd, Bengaluru

Fax: (080) 43002333

Phone: 43002000

Web: www.analog.com

16- & 32-bit microcontrollers

Fujitsu Semiconductor has released two series of microcontrollers. The MB96600 series of 16-bit microcontrollers consists of 53 different products, ranging between 48-144 pin packages and 32KB-384 kB of Flash memory. The MB91520 series of 32-bit microcontrollers consists of 60 different products, ranging between 64-176 pin packages and 256 kB-1MB of Flash memory.

The line-up comes with a low-voltage detection circuit, a CR oscillation circuit and a hardware watchdog circuit. The chips also have an analogue-to-digital converter and assistance features for LIN hardware, including automatic check-sum and self-diagnosis functionality.

Fujitsu Semiconductor Asia Pte Ltd, Bengaluru

Fax: (080) 28416660

Phone: 28419990

Web: www.fujitsu.com

Digital signal controllers

Microchip Technology has introduced 60 MIPS 16-bit dsPIC digital signal controllers (DSCs). Based on the next-generation dsPIC DSC/PIC24 MCU core, the dsPIC33E offers 536kB Flash memory, 52kB RAM, 144-pin input/output packages and USB 2.0 on-the-go (OTG) interface.



The dsPIC33E devices include four SPI and UART interfaces, two I²C interfaces and an auxiliary Flash module. The USB 2.0 OTG peripheral enables connection to a PC, Flash drive and other USB-enabled devices. The 60 MIPS performance enables support for commercial applications such as servo motor control, solar inverters, and running dual 3-phase motors in parallel.

Microchip Technology (India) Pvt Ltd,

New Delhi

Fax: (011) 51608632

Phone: 41608631

Web: www.microchipdirect.com

LIGHTING

Search light

Binay Opto has come up with PowerLED search/flood light.

Model 3618L has a life of 100,000 hours and power consumption around



65 watts. The PowerLED is shock-resistant and vibration-proof due to its solid-state LED construction.

It is housed in die-cast aluminium alloy IP55 or IP65 protection.

The PowerLED is covered in 5mm-thick tempered protective toughened glass, which is shock and impact resistant. All Power LEDs are provided with lenses to provide focused light to various angles.

Binay Opto Electronics Pvt Ltd, Kolkata

Fax: (033) 22421493

Phone: 22429082, 22103807

E-mail: info@binayled.com, binay@vsnl.com

Passive infrared motion sensor

Highly Components has introduced passive infrared (PIR) motion sensor for automatic light control. The sensor is a fully-automatic indoor and outdoor security/courtesy light controller capable of controlling up to 2000 watt incandescent or 30 watt×20 fluorescent of lighting in day as well as at night.



The built-in PIR motion sensor turns on the connected lighting system

when it detects motion in its coverage area. During the day, the built-in photocell sensor saves electricity by deactivating the lights. An adjustable time knob lets you select how long the light stays on after activation. In the evening or at night, it can be managed that at what time the lights should be switched on by the LUX adjustment knob provided in the sensor.

Highly Components Pvt Ltd, New Delhi

Fax: (011) 27461984

Phone: 27245389, 27249931, 27451984

E-mail: highlycomponents@gmail.com, sales@pirsensors.com, hepl@bol.net.in

Web: www.energysavingsensors.com, www.pirsensors.com, www.hamiltonindia.com

COMPUTING

Motherboard

ASUS has launched the F1A75 series motherboards.

The motherboards are based on AMD A75 chipset and FM1 socket, which supports AMD's new APUs.



These include AMD Radeon HD 6000 series processor graphics with AMD Dual Graphics support. The series also supports USB 3.0 and SATA 6Gbps standards.

Included on all F1A75 series motherboards is the UEFI BIOS menu interface, which allows users to control and adjust their BIOS settings through a mouse-enabled interface. The built-in EZ Mode option also provides a drag-and-drop boot priority option for management of boot devices, while the Advanced Mode allows to tweak more intricate system settings.