

Power Packed Resistors From

WIRE WOUND RESISTORS



HIA

Power Axial type.
Power Rating : 0.5W to 20W
Resistance Range : R01 to 120K
Tolerances Available : 10%, 5%, 3%, 1%
Features : • Flame retardant. • Pulse type available. • Thermocot precision power. • Non-inductive type available.

HFP

Power type PCB mounting.
Power Rating : 2W to 8W (at 70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%
Features : • Low cost. • Automated assembly and wave soldering possible. • Commercial applications.

HSR

Capacitor discharge,
Wire wound symmetry resistors
Power Rating : 8.25W & 11W (70°C)
Resistance Range : 10K to 70K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Stainless steel mounting terminals for direct mounting on to capacitors.

HCA/HCV

Power Axial type
Power Rating : 1W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • High insulation • Fire proof. • Resistant to aggressive solvents. • Pulse type available. • Bracket acts as heat sink.

HI-TECH RESISTORS PVT. LTD.

AN ISO TS 16949: 2009 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA.
Tel: + 91-712-2531134, 2533269, 2553691. Fax: + 91-712-2528334, 2556351.
e-mail : info@htr-india.com | www.htr-india.com

CURRENT SENSE RESISTORS

OA / OP

Open Frame / Axial and PCB Mounting - Shunt Type.
Power Rating : 0.5W to 5W (85°C)
Resistance Range : R002 to R10
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Non insulated. • Surge / current sensing applications.

RL

Alloy ribbon element in cylindrical ceramic body.
Axial type.
Power Rating : 0.5W to 10W (25°C)
Resistance Range : R002 to R80
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Negligible inductance. • Replaces moulded type.

BR

Slim type Metal Plate / Preformed Resistance Strip.
Power Rating : 2W to 10W (70°C)
Resistance Range : R01 to 1R2
Tolerances Available : 10%, 5%
Features : • Radial configuration. • Negligible inductance. • Choice of 3 different preforms available.

FUSIBLE RESISTORS (Safety Version)

FRS

Wire wound type.
Power Rating : 1W to 5W
Resistance Range : 10R to 3K3
Tolerances Available : 10%, 5%
Features : • Fire retardant coating. • UL requirements met satisfactorily. • Fail safe 'safety version' available.



Metaphors

SMD ELECTRO COMPONENTS

Full Range of SMD Active & Passive Components

Authorised Distributor

leaguer	SMD I-Capacitors
KEXIN	SMD Transistors SMD QFN SMD Diodes SMD Capacitors
walfts	SMD Resistors

CHIP TRANSISTORS / CHIP DIODES / CHIP LED's / CHIP CAPACITORS / CHIP IC's

- CHIP RESISTORS - CHIP RESISTOR NETWORKS - CHIP CAPACITORS - CHIP TANTALUM CAPACITORS - CHIP ELECTROLYTIC CAPACITORS - CHIP ZENERS & DIODES - CHIP TRANSISTORS - CHIP LED'S - CHIP SCHOTTKY DIODES	- CHIP BRIDGE RECTIFIERS - CHIP TRANSIENT VOLTAGE SUPPRESSORS - CHIP IC'S - CHIP MOSFETS - CHIP REGULATORS - CHIP OPTO COUPLERS - CHIP TRIMMER CAPACITORS - CHIP INDUCTORS	- CHIP FERRITE BEADS - CHIP HALL SENSORS - CHIP IN LEDS & SENSORS - CHIP POTENTIOMETERS - CHIP FUSES - CHIP SWITCH - CHIP MOV'S - CHIP THERMISTORS - CHIP SOLDER PASTE - CHIP SOLDER WIRE 26 SWG
---	---	---

PHILIPS, intel, IOR, NEC, HYBRON, KEMET, Panasonic, HITACHI, ROHM, TDK, ZENITH, MOTOROLA

54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road, Mumbai - 400 007, INDIA. Tel. : 91-22-3240 2444 • Mob. : 93242 11912

E-mail : smdelectro@vsnl.net

FOR ALL YOUR ELECTRONIC COMPONENTS NEED

www.icsemiconductor.com

Visit us:

electronica India 2011 & productronica India 2011

Exhibition

HALL NO. 12 A, BOOTH NO. 2021 / 2023
PRAGATI MAIDAN, NEW DELHI
DATES: 13th TO 16th SEPT 2011