

NEW!

Five Stars: Ultra-Compact Low Profile AC/DC Power Supply

AC/DC Power Converter Exceeding Worldwide Standby Power Standards

- ✓ Ultra-low 30mW Standby Power Consumption
- ✓ 1W ~ 6W PCB Mount Package
- ✓ Extra Wide Input Voltage Range (90~277VAC)
- ✓ Class II Power Supply with 3kVAC Isolation
- ✓ -25°C to +85°C Operating Temperature
- ✓ Low Output Ripple
- ✓ Short Circuit Protected Outputs
- ✓ UL, EN & CE Certified
- ✓ Single or Dual Output Options

The RAC01 and RAC02 have a miniscule no load power consumption of only 30mW, while the RAC03 uses less than a tenth and the RAC06 only half of the standby energy specified in the existing EPA Energystar, CEC, CECP and the European EuP guidelines. This ultra-low power consumption means that the converters will still comfortably meet the future standby consumption limits of 500mW when the standards are revised in 2013.



The New RAC Series:
Ultra-low power consumption
to meet the European EuP
guidelines.

No-load consumption score chart Five stars = most energy efficient

★★★★★	>0.03W	RECOM
★★★★	>0.03W to 0.15W	
★★★	>0.15W to 0.25W	
★★	>0.25W to 0.35W	
★	>0.35W to 0.5W	
no stars	>0.5W	

Source: Energy Star



electronica India 2011

September 13 - 16, 2011
New Delhi, Pragati Maidan
Hall 12A, Booth 2285

Authorised India Representatives:



ARROW ASIA PAC LTD.



Omniscient
Electronics Pvt. Ltd.,

RECOM
www.recomasia.com