

range and is available in 8-pin SOT23 and μ MAX packages.

Maxim India, Bengaluru

Fax: (080) 3028 5812

Phone: 3028 5800

Web: www.maxim-in.com

Multi-LED driver

ON Semiconductor has introduced a multi-LED driver with the ability to drive up to eight LEDs independently, using any illumination pattern that the user creates.

With the NCP1840, current and dimming level programming is done by writing to and reading registers via a serial interface that controls the brightness and blink rate of each LED. LED brightness levels can be controlled logarithmically to accommodate natural eye viewing with no brightness distortion. The device requires five small ceramic capacitors and one resistor to form a complete LED power supply and current controller.

The NCP1840 comes in a lead-free, RoHS-compliant 4x4mm² package, and operates over a temperature range of -40°C to +85°C.

Arrow Electronics India Pvt Ltd, Noida

Fax: (0120) 4535505

Phone: 4535500

Web: www.arrowasia.com

TOOLS & EQUIPMENT

Ethernet rackmount switch

Kontron has introduced a 10-gigabit Ethernet (GbE) rackmount switch with up to 32 ports. Based on Kontron's



10GbE compact PCI switch CP6930, the CP6930-RM provides a ready-to-run rack-mounted unit including redundant AC or DC power options.

The switch offers up to six 10GbE ports and up to 26 1GbE ports. Up to six 10GbE ports are directly accessible on

the front via SFP+, plus two 1GbE ports over SFP. The CP6930-RM provides a rich feature set of Layer 2 (L2) and Layer 3 (L3) functions, such as IP forwarding, L2 and L3 multicast, quality of service and virtual local-area networks.

Kontron Technology India Pvt Ltd, Bengaluru

Fax: (080) 40831001

Phone: 40831000

Web: www.kontron.com

PCI-Express interface board

Buffalo Technology has launched a PCI-Express interface board with four USB 3.0 ports. USB 3.0 transfers data at



up to 5 Gbps. Four ports allow simultaneous connection of more external HDDs, SSDs, flash memory and other devices.

The board is fully backward-compatible with USB 2.0 devices. The driver supports Windows Server, Windows 7, Vista and XP OS. An internal power cable is also included.

Buffalo Inc., New Delhi

Fax: (011) 41538069

Phone: 41538059


E-mail: info-india@melcoinc.co.jp

Web: www.buffalo-asia.com

Design and simulation platforms

Agilent Technologies Inc. has released new versions of its Advanced Design System (ADS) and Electromagnetic Professional (EMPro) software.

The ADS 2011.10 electronic design automation software provides users with a design documentation notebook



that makes it easy to create and share all or selected views of schematics, layout and data displays, and generate PDF and postscript outputs files.

The EMPro 2011.11 3D modeling and simulation platform is used to create 3D models and analyse electrical performance of packages, connectors, antennae and other RF components.

Agilent Technologies India Pvt Ltd, New Delhi

Phone: (0124) 229009

E-mail: tm_india@agilent.com

Web: www.agilent.com

TEST & MEASUREMENT

Thermal imager

Ideal Industries has released Heat-Seeker 160 thermal imaging camera that features a Class II laser and an 8.9cm (3.5-inch) LCD screen. The imager delivers a high-resolution (160x120-pixel) thermal image and a 2-megapixel visual image in a temperature range of -10°C to 250°C (14°F to



482°F) with an industry-standard accuracy of $\pm 2^\circ\text{C}$.

The camera is fully radiometric and captures temperature measurements over the entire image. It has a removable 2GB micro SD memory card and an inbuilt LED light for dim-lit environments. The camera comes with a field-replaceable, rechargeable Li-ion battery capable of up to five hours of continuous operation.

Ideal Industries India Pvt Ltd, Gurgaon

Phone: (011) 244308254

E-mail: Rakesh.Batra@ideal-industries.in

Web: www.idealindustries.com

High-voltage digital insulation tester

Minoo Impex has added a high-voltage insulation tester to its Metrix+ family.

The DIT 3125 can measure up to 5 kV range and has a backlit LCD. The instrument features auto-discharge function and live-circuit warning sym-