



bols with audio and low-voltage indication. Polarisation index can be measured by automatic measurement function of the ratio of the resistance in arbitrary two-point time.

Measurement data can be downloaded to a PC via USB data cable and the included software.

Mino Impex, Kolkata

Phone: (033) 22309888

E-mail: metrixinstrument@gmail.com

POWER

DC power supply

Scientific has launched a DC power supply with 0-32V, 10A DC output delivering 320 watts of power.



The device is equipped with an optional interface that allows users to control the power supply unit remotely with load data logging. The output voltage can be set independently without disconnecting the load. The unit can be switched on or off from the front panel or with the remote.

Scientific Mes-Technik Pvt Ltd, Indore

E-mail: marketing@scientificindia.com

Web: www.scientificindia.com

Battery charger

GlacialTech Inc. has introduced GP series battery chargers. The FA1210 and FA2407



have input rated current of 3.5A and 3A and charge 12V/10A and 24V/7A batteries, respectively. In addition to the inbuilt charger function, these provide power supply mode for all electronic products in the car.

The charger offers 2V-15V charging voltage for deep-discharge and dead batteries and has eight microprocessor-controlled charging stages. It features over-voltage protection, short-circuit protection, over-temperature protection, reverse-polarity protection and wrong-battery protection.

Lotus Insulation Services, Pune

E-mail: sales@lotusin.co.in

Web: www.GlacialLight.com

COMPUTING

Motherboards

Gigabyte Technology has launched X79 series motherboards, which support the second-generation Intel Core i7 processor family for high-end desktops. Featuring the LGA 2011 socket and based on updated micro-architecture, these processors feature up to six cores with up to 15MB L3 cache, four-channel DDR3 memory and 40 PCI Express lanes. The motherboards employ Gigabyte 3D Power and Gigabyte 3D BIOS.

The Gigabyte 3D Power application allows load-line calibration adjustment, over-voltage protection control, and real-time adjustment of CPU, VTT, IMC and four-channel memory frequencies via a graphical user-interface. Gigabyte 3D BIOS provides an advanced mode for veteran BIOS users, alongside a graphical 3D mode.

Gigabyte Technology India Pvt Ltd, Mumbai

Fax: (022) 40633223

Phone: 40633222

Web: www.gigabyte.in

MISCELLANEOUS

USB 3.0 Flash drive

ADATA Technology has launched three models of ADATA USB 3.0 Flash drive—N005 Pro, S102 Pro and C103.

The N005 Pro is available in 8GB and 64GB capacities and offers sequential



read and write speed of up to 180 MB/s and 90 MB/s, respectively. The S102 Pro comes in 8GB and 32GB capacities with sequential read and write speed of up to 100 MB/s and 50 MB/s, while the C103 is available in 8GB and 16GB capacities with sequential read and write speed of up to 90 MB/s and 10 MB/s, respectively.

ADATA Technology (India) Pvt Ltd, Mumbai

Fax: (022) 67587045


Phone: 67587045

E-mail: adata_in@adata-group.com

Web: www.adata.co.in

Reference platform

Freescale Semiconductor has introduced a home health hub (HHH) reference platform to help medical equip-



ment manufacturers create remote-access devices that can collect, connect and share health data for healthcare management.

The HHH reference platform consists of an aggregator/gateway board based on the low-power i.MX28 applications processor, ZigBee and sub-1GHz transceivers and can provide wired and wireless connectivity to healthcare devices. It enables secure Wi-Fi and Ethernet connectivity to remote devices with displays, such as tablets, smartphones or PCs with medical-specific remote user interface options.

Freescale Semiconductor India Pvt Ltd, Noida

E-mail: salesindia@freescale.com

Web: www.freescale.com