

Power Packed Resistors From

WIRE WOUND RESISTORS



CURRENT SENSE RESISTORS

HMV

Flat vertical mounting type.
Power Rating : 2.5W to 15W (70°C)
Resistance Range : R10 to 36K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Ceramic legs act as heat sink.
• Slim profile. • Space saver.
• Pulse type available.
Available in low ohm current sense type as HMVL series.



HEA

Semi precision Axial Type.
Power Rating : 2.5W to 17W (70°C)
Resistance Range : R025 to 70K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Low surface temperature.
• Fire retardant. • Pulse type available.



OA / OP

Open Frame / Axial and PCB Mounting - Shunt Type.
Power Rating : 0.5W to 5W (85°C)
Resistance Range : R002 to R10
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Non insulated.
• Surge / current sensing applications.



HEAL

Alloy Ribbon Element / Axial Type.
Square Profile Ceramic Tube.
Power Rating : 2.5W to 12W (70°C)
Resistance Range : R0025 to R20
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Negligible inductance.
• Surge / current sensing applications.



HCP

Power Type.
PCB Mounting.
Power Rating : 3W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%
Features : • Inverter / Power Supplier application. • Adaptable to automated assembly. • Choice of terminal stand-off heights. • Choice of terminal to suit exact PCB requirements.



HIA

Power Axial Type.
Power Rating : 0.5W to 20W
Resistance Range : R01 to 120K
Tolerances Available : 10%, 5%, 3%, 1%
Features : • Flame retardant
• Thermocoat precision power
• Pulse type available.
• Non-inductive type available.



BR

Slim type Metal Plate / Preformed Resistance Strip.
Power Rating : 2W to 10W (70°C)
Resistance Range : R01 to 1R2
Tolerances Available : 10%, 5%
Features : • Radial configuration
• Negligible inductance. • Choice of 3 different preformings available.



OFSC

PCB Mounting.
Power Rating : 5W & 10W (70°C)
Resistance Range : R00012 to R003
Tolerances Available : 5%, 3%, 2%, 1.5%, 1%
Features : • Silicone coated.
• Surge / current sensing applications.
• Negligible inductance.



HI-TECH RESISTORS PVT. LTD.

AN ISO 9001:2002 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA Tel. : + 91-712-2531134, 2533269, 2553691.
Fax : +91-712-2528334, 2556351. e-mail : info@htr-india.com | www.htr-india.com

Nagpur

SMD ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE & PASSIVE COMPONENTS

Authorised Distributor

leaguer SMD Capacitors

KEXIN SMD Transistors
SMD LDR SMD Diodes
SMD Capacitors

watts SMD Resistors

CHIP TRANSISTORS / CHIP DIODES / CHIP LED's / CHIP CAPACITORS / CHIP IC's

• CHIP RESISTORS	• CHIP BRIDGE RECTIFIERS	• CHIP FERRITE BEADS
• CHIP RESISTOR NETWORKS	• CHIP TRANSIENT VOLTAGE SUPPRESSORS	• CHIP HALL SENSORS
• CHIP CAPACITORS	• CHIP IC'S	• CHIP IR LED'S & SENSORS
• CHIP TANTALUM CAPACITORS	• CHIP MOSFETS	• CHIP POTENTIOMETERS
• CHIP ELECTROLYTIC CAPACITORS	• CHIP REGULATORS	• CHIP FUSES
• CHIP ZENERS & DIODES	• CHIP OPTO COUPLERS	• CHIP SWITCH
• CHIP TRANSISTORS	• CHIP TRIMMER CAPACITORS	• CHIP MOV'S
• CHIP LED'S	• CHIP INDUCTORS	• CHIP THERMISTORS
• CHIP SCHOTTKY DIODES		• CHIP SOLDER PASTE
		• CHIP SOLDER WIRE 26 SWG.

54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road, Mumbai - 400 007, INDIA. Tel. : 91-22-3240 2444 • Mob. : 93242 11912

E-mail : smdelectro@vsnl.net

STOCKIST OF ELECTRONIC COMPONENTS

Circuit Electro-Components Pvt. Ltd.

"Drug House", Bldg. 54-B, Proctor Road, Mumbai - 7, INDIA.
Pin Code : 400 007 • Tel. : 2387 7777 / 2380 0888
Mob. : 93222 34370 / 93227 81112 • Fax : 91-22-2387 9330
E-mail : cirkil@vsnl.com • Website : www.cirkilelectro.com

HODAY SERVICE AVAILABLE