



er management technology that dynamically adjusts power draw on the fly.

The HD 6970 and HD 6950 graphics cards offer a superb visual experience using flexible and cost-effective AMD Eyefinity multi-display technology and AMD HD3D technology for 3D entertainment.

AMD Far East Ltd, New Delhi

Fax: (011) 41672623

Phone: 41672614

## COMPONENTS

### Hot-swap I<sup>2</sup>C multiplexers

Linear Technology has introduced two-wire bus multiplexers that provide individual enable pins to connect an upstream I<sup>2</sup>C bus to any combination of downstream buses or cards.

The multiplexers are pin-selectable with bus buffers that reduce component count while promoting ideal I<sup>2</sup>C signal integrity. The LTC4312 multiplexes two channels, while the LTC4314 multiplexes four channels. These devices allow easy I<sup>2</sup>C address expansion, providing the ability to address one of multiple identical devices, thus resolving address conflict issues. Bidirectional capacitive buffering allows extension of the I<sup>2</sup>C bus size well beyond the 400pF I<sup>2</sup>C bus specification and prevents I<sup>2</sup>C signal corruption during live board insertion or removal.

The LTC4312 and LTC4314 are suitable for a wide range of applications, including radial architectures in telecom systems such as ATCA, address expansion and level translators.

Arrow Electronics India Ltd, Bengaluru

Fax: (080) 51127784

Phone: 51353800

### Metal-film resistors

Vishay Intertechnology has released a new surface-mount series of high-precision, high-stability metal-film resistors in 2012 and 4527 case sizes. For excellent stability across a range of environmental conditions, the PSF re-

sistors feature extremely low temperature coefficients down to  $\pm 5$  ppm/°C and tight tolerances to 0.01 per cent.

The PSF2012 offers a 0.125W power rating and 200V working voltage, while the PSF4527 features a 0.25W power rating and 300V working voltage.

Compliant wraparound terminations eliminate the risk of solder fillet cracking due to differences in the coefficient of thermal expansion. A rugged moulded encapsulation optimises performance in harsh environments.

The devices operate over a temperature range of -55°C to +150°C.

Vishay Components India Pvt Ltd, Bengaluru

Fax: (080) 25584291

Phone: 25586277

E-mail: business-asia@Vishay.com

### System-on-chip ICs

STMicroelectronics has unveiled two new system-on-chip ICs that allow standard-definition (SD) or high-definition (HD) equipment to share the same printed-circuit-board (PCB) design and leverage software developed for earlier product generations.

The STi7162 for HD STBs and STi5262 for SD products are based on the widely used STi7167 and STi5267, respectively. Targeting free-to-air, cable and terrestrial STBs, as well as hybrid products with added support for IPTV, each device combines the STB decoder with DVB-C cable and DVB-T terrestrial demodulators, plus optional Ethernet support. The devices support targeted functions for cost-optimised STBs with built-in security features.

The STi7162 and STi5262 have identical pin assignments, allowing manufacturers to save the costs of developing a separate PCB for SD and HD products.

STMicroelectronics Marketing Pvt Ltd, Noida, Uttar Pradesh

Fax: (0120) 4243417

Phone: 4243400

### Isolated DC-to-DC converter

Analog Devices, Inc. claims to have announced the industry's smallest

isolated DC-to-DC converter. Offering a 5kVrms isolation rating in a 1×1cm<sup>2</sup> package, the ADuM6000 is a 0.5W device that integrates ADI's proprietary iCoupler digital isolation technology and isoPower DC-to-DC converter. It allows designers to free up valuable circuit-board real estate while eliminating the time-consuming step of securing medical or other safety approvals (such as IEC-60601-1)—all at a fraction of the cost of alternative devices, including optocouplers.

Analog Devices India Pvt Ltd, Bengaluru

Fax: (080) 25216452

Phone: 41194300

E-mail: india.custserv@analog.com

## SOFTWARE

### 3D anatomy software

The Cyber Anatomy Med VR software introduced by Dispro Visual Technologies creates a three-dimensional (3D), virtual-reality model of the complete human body. More than 13,000 body parts are displayed in full-colour, medically accurate details. This enables one to show spatial relationship between the bones, muscles, arteries, veins and nerves that one finds in an actual cadaver.

The 3D model allows multiple students to perform the same exercise—something that would not be possible using an actual cadaver. Doctors, teachers and other health professionals using this 3D product are able to advance students' core curriculum and understanding of the human body, without fully relying on actual cadavers or sacrificing precious cadaver organs.

Cyber-Anatomy's real-time simulation environment makes a full set of interactive functions available. Rotation, dissecting, zooming in/out, peeling away skin, labelling and focusing on any specific organ are just a few examples of the flexibility allowed to students.

Dispro Visual Technologies Ltd, Hyderabad

Phone: (040) 64523140, 66627045

E-mail: info@disprovisual.com,

disprovisual@gmail.com