



Fanless Intel® Atom™ D525 Processor Family

Dual Core Embedded Platform



- uEFI BIOS support fast boot, HDD capacities more than 2.2 TB
- DDR3-800 MHz supports up to 4 GB
- TPM support
- ASF 2.0 support



AFL GEN II 12" Panel PC



AFL2-12-D525

Fanless Embedded Solutions



ECW-281B-D525
Extended temperature support



TANK-101B
Isolated COM & CAN Bus



TANK-101B
Compact size 180x138x50mm

Full-size PICMG 1.0



WSB-PV-D525

Half-size



PICOe/PCISA-PV-D525

Mini ITX KINO Series



KINO-PV-D525

5.25" NOVA Series



NOVA-PV-D525

EPIC NANO Series



NANO-PV-D525

3.5" WAFER Series



WAFER-PV-D525

CPU Module



ICE-PV-D525



PM-PV-D525

IP 67 Solution



SAILORPC-12A

12.1" IP67 Rated Robust Panel PC

- Intel® Atom™ Extra Low Power Processor
- 12.1" watertight enclosure and connectors allow immersion up to 1m depth for 30 minutes
- Regular 400 nits/1000 nits sunlight readable TFT LCD display with resistive touch panel



WSrider-200A

IP67 Protection Embedded Controller

- Intel® Atom™ Z510P solution
- IP67 compliant rugged design
- Built-in 802.11b/g/n high speed wireless communication
- 9-28VDC power input
- Two channels analog video input
- IEI One Key Recovery solution allows you to create rapid OS backup and recovery
- Wide Temp. design (-30°C ~ 70°C)

Mobile Solution



MODAT-200

Ordering Entry PDA

- Table Service
- Quick Registration
- Inspection
- On-line Sales



Ice-ROCK-08A

Infotainment Tablet PC

- Ambient Light Sensor
- Rotate with G-Senso
- 8 Programmable Function Keys
- Hot Keys Control
- 1.3 Mega pixel Camera and Microphone

IEI Technology Corp.

No.29, Jhongsing Rd., Sijhih City, Taipei County 221, Taiwan
TEL: 886-2-8691-6798 | FAX: 886-2-6616-0028 | email: sendhilkumar@iei.com.tw

www.ieiworld.com