

New Products

TEST & MEASUREMENT

Protocol analyser

JISL has introduced AstroDesign model protocol analyser. The VA-1831 HDMI 1.4 enables checking of the protocol parts required in the



development of HDMI transmission equipment. Using its front-panel LCD monitor and internal speaker, HDMI images and sound can be checked.

The performance information (EDID, SINK) of the VA-1831 can be rewritten so that various kinds of receivers (monitors) can be virtualised. The unit can also be used as a repeater by channeling the signals through its HDMI output connector.

Jay Instruments & Systems Pvt Ltd, Mumbai.

Fax: (022) 23526210

Phone: 23526207

E-mail: marketing@jayinst.com

Web: www.jayinst.com

Network analyser

Agilent Technologies has introduced five new PNA microwave vector network analyser models.



The PNA series is based on the company's PNA-X architecture and is available with two-port internal single-source or four-port internal dual-source configuration in five frequency models—13.5, 26.5, 43.5, 50 and 67 GHz.

The 0.1dB receiver compression point is higher than +10dBm for all models. The highest source output power is +11 dBm at 67 GHz (N5227A 67 GHz model).

Agilent Technologies India Pvt Ltd, New Delhi

Phone: (0124) 229 009

E-mail: tm_india@agilent.com

Web: www.agilent.com

TOOLS & EQUIPMENT

Wireless router

Buffalo Technology has introduced AirStation high power N150 wireless router and access point model WCR-HP-GN.

The solution is powered by DD-WRT—Open Source firmware for optimising wireless performance, security and routing options, and has a 5dBi-gain detachable antenna.

It is loaded with AirStation one-touch secure system (AOSS) which wirelessly connects it to other AOSS devices. WCR-HP-GN offers wireless security support including WPA2, WPA-PSK (TKIP, AES) and WEP (128/64bit).

Buffalo Inc., New Delhi

Fax: (011) 41538069

Phone: 41538059

E-mail: info-india@melcoinc.co.jp

Web: www.buffalo-asia.com

COMMUNICATION

Controller area network module

National Instruments has added NI 9862 C series high-speed controller area network (CAN) module to its NI-



XNET family of interfaces designed to communicate with embedded networks.

The module expands the NI-XNET family to the NI Compact-

DAQ and CompactRIO hardware platforms and introduces CAN support to NI CompactDAQ. The NI 9862 provides sustained transfer rates up to 1Mbps.

The NI CompactDAQ platform provides portable CAN communication with the availability of 4- and 8-slot USB or Ethernet chassis and is compatible with more than 50 other NI C Series input/output (I/O) modules.

NI Systems (India) Pvt Ltd, Bengaluru

Phone: (080) 41190000

E-mail: ni.india@ni.com

PCI Express and Ethernet hybrid switch

Kontron has introduced 3U OpenVPX PCI Express and Ethernet hybrid switch which delivers high transfer rates in centralised VPX and OpenVPX platforms.

The VX3905 is compliant with the OpenVPX VITA65 switch slot profile SLT3-SWH-6F6U-14.4 for compatibility in multi-board designs. It provides up to 24 PCI Express Gen 1/Gen 2 ports for up to 32 lanes which can be configured (x8, x4, x2 and x1) depending on the required bandwidth.

The switch can also be partitioned into multiple PCI Express subsystems in order for the centralised backplane to host multiple root complexes each being able to control their own peripherals.

Kontron Technology India Pvt Ltd, Bengaluru

Phone: (080) 40972761/62

Web: www.kontron.com