

mable switching DC power supply covering a power range up to 1080 watts.



The PSW-Series includes six models with the combination of 30V and 80V rated voltages and 360 watts, 720 watts and 1080 watts maximum output powers. The PSW units can be connected in series or parallel and offer adjustable slew rates to meet the requirements of voltage/current level transition tests.

Good Will Instrument Co. Ltd
E-mail: marketing@goodwill.com.tw
Web: www.gwinstek.com

Graphics card

AMD has introduced its newest-generation professional graphics cards—AMD FirePro V5900 and AMD FirePro V7900.



The graphics cards offer AMD PowerTune technology that provides direct control over GPU power-usage. These also have Eyefinity multi-display support. The FirePro V7900 and FirePro V5900 support up to four and three displays respectively. The GeometryBoost technology processes two primitives per clock cycle.

The graphics cards also feature DisplayPort 1.2, HDMI 1.4 support and 2GB GDDR5 frame buffer.

AMD India, Gurgaon
Fax: (0124) 4696177
Phone: 4696000
Web: www.amd.com

Simulation environment

COMSOL Inc. has launched its latest version of COMSOL Multiphysics

simulation environment.

The Version 4.2 comes with three new application modules—microfluidics, geomechanics, and electrodeposition—and new LiveLink interfaces for AutoCAD and SpaceClaim.

Microfluidics module brings easy-to-use tools for the study of microfluidic devices and rarefied gas flows, Geomechanics module enables multi-physics modeling in geotechnical applications, while

Electrodeposition module helps in electrochemical processes for chrome plating, e-coating, electro-colouring, decorative electroplating, and electrodeposition.

COMSOL India, Bengaluru
Fax: (080) 40923856
Phone: 25597799
E-mail: info@comsol.com
Web: www.comsol.com

LED tubelight

Binay Opto has introduced PowerLED tubelight. The 42L-C-4 does not use small-chip (SMD/5mm/4-leg) LEDs, but is designed with high-illumination Power LEDs having a life of 50,000 hours to 100,000 hours.

This model's light output of 2600 utilised scotopic-source lumens is of a homogenous nature, and it provides flicker-free operation from 170V-230VAC. The 42L-C-4 consumes 14-15 watts power and has a colour rendering index of 75.



The product is designed for direct fitting into an existing standard fluorescent tubelight luminaire or strip, after removing the starter and shorting the existing electromagnetic choke/ballast terminals.

Binay Opto Electronics Pvt Ltd, Kolkata
Fax: (033) 22421493
Phone: 22429082, 22103807
E-mail: info@binayopto.com, binay@vsnl.com

Fingerprint scanner

BioEnable Technologies has introduced a ten fingerprint scanner which has been certified by Standardization, Testing and Quality Certification (STQC)—certification body for UID.

The 134×151×125mm³ scanner acquires four-slap/two-thumb as well as rolled fingerprints. It integrates twelve LED user-graphical-interfaces and Green Bit software.

The 2kg scanner has a USB 2.0 interface, and operating temperature from 1.5°C to 49°C.

BioEnable Technologies Pvt Ltd, Pune
Fax: (020) 26898686
Phone: 66813660
E-mail: sales@bioenabletech.com
Web: www.bioenabletech.com

Movement sensor

Ideas Unlimited has introduced MS101 series of movement sensor switches.



The external mounting-type sensor switches are designed for installation in buildings and homes that are completed with electrical wiring already in place. The series include five different types of models—wide, medium and narrow.

The models have different sensor ranges and load capacities of 500W and 1000W. These are recommended for lighting and fan control applications.

Ideas Unlimited, Mysore
Phone: (0821) 2402979
Web: www.ideas-unlimited.in